

RENCANA PEMBELAJARAN SEMESTER
(RPS)

Mata kuliah : Basis Data Lanjut
Kode Mata Kuliah : TIK
S K S : 3 SKS
Prodi Konsentrasi : Sistem Informasi
Semester : 5
Kode Dosen : 196404091995121001

MATA KULIAH: Basis Data Lanjut



PROGRAM STUDI S1 SISTEM INFORMASI

FAKULTAS TEKNOLOGI INFORMASI
UNIVERSITAS ANDALAS

2017

A. Deskripsi Mata Kuliah

Mata kuliah ini membahas tentang basis data spasial PostGreSQL/PostGIS dan pemakaian perintah-perintah operasi spasial PostGIS di dalam mengembangkan satu sistem informasi spasial.

B. Capaian Pembelajaran (Kompetensi yang diharapkan)

Capaian pembelajaran mata kuliah :

1. Mahasiswa mampu memahami basis data PostGreSQL /PostGIS untuk mengembangkan sistem informasi spasial
2. Mahasiswa mampu memahami sistem informasi spasial yang ada.
3. Mahasiswa mampu mengembangkan sistem informasi spasial yang ada.

C. Capaian Pembelajaran dan Materi Pembahasan setiap pertemuan

Pertemuan	Kemampuan akhir yg diharapkan	Materi Pembelajaran (Bahan Kajian)
1, 2,3,4	Mhs mampu memahami basis data PostGreSQL /PostGIS untuk mengembangkan sistem informasi spasial	Database PostgreSQL dan PostGIS
5, 6, 7	Mhs mampu memahami sistem informasi spasial yang ada.	Aplikasi GIS untuk masjid, kuliner, tanah dan penduduk
8	Evaluasi Tengah Semester	
9, 10, 11, 12, 13, 14, 15	Mhs mampu mengembangkan sistem informasi spasial yang ada	Pengembangan Aplikasi GIS untuk masjid, kuliner, tanah dan penduduk
16	Evaluasi Akhir Semester	

D. Kemampuan Akhir Hard skills dan Softskill melalui Mata Kuliah

Kemampuan Hardskills	Kemampuan Softskills:
<ol style="list-style-type: none"> 1. memahami basis data PostGreSQL /PostGIS untuk mengembangkan sistem informasi spasial 2. memahami sistem informasi spasial yang ada. 3. mengembangkan sistem informasi spasial yang ada 	<ol style="list-style-type: none"> 1. Bekerjasama dalam tim 2. Komunikasi secara efektif

E. Strategi Perkuliahan

Perkuliahan akan diberikan dalam 14 kali pertemuan, termasuk di dalamnya ujian tengah semester (UTS) dan ujian akhir semester (UAS) berupa penyerahan laporan tugas besar. Kegiatan tatap muka diisi dengan diskusi, presentasi dan tugas aplikasi. Kegiatan mandiri diisi dengan penelaahan/pengkajian teori pada buku/literatur yang dianjurkan. Kegiatan mandiri ini **wajib** dilakukan oleh setiap peserta di luar kegiatan tatap muka. Kegiatan terstruktur diisi dengan tugas-tugas pengayaan dan pendalaman. Kehadiran mahasiswa dalam perkuliahan minimal **75 persen** dari jumlah pertemuan yang diselenggarakan.

F. Evaluasi Perkuliahan

Keberhasilan dalam mengikuti mata kuliah ini didasarkan atas penilaian terhadap hasil-hasil pekerjaan mahasiswa, yang memenuhi persyaratan kehadiran minimal 75%, ujian tengah semester (bobot 1), dan ujian akhir semester (bobot 2). Skor akhir akan diolah dengan menggunakan Acuan Patokan, dan dikonversi ke dalam nilai A B C D E.


G. Sumber rujukan

1. PostGreSQL
 2. PostGIS.
 3. Aplikasi GIS untuk mesjid, kuliner, penduduk dan bangunan (Hasil riset)

H. Penanggung Jawab Matakuliah

1. Pengampu mata kuliahan

Prof. Dr. Surya Afnarius



2	Mahasiswa mampu memahami sistem informasi spasial yang ada (P1, P2, KU2, KU10)
3	Mahasiswa mampu mengembangkan sistem informasi spasial yang ada (S9, KU2, KU10, KU11, KK3)
4	Mahasiswa memiliki kemampuan softskill dalam pembelajaran berupa: <ul style="list-style-type: none"> - Mampu berkomunikasi lisan dengan baik - Mampu bekerja sama dalam kelompok - Mampu mengejola / leadership dalam kelompok.
Deskripsi Singkat Mata Kuliah	Mata kuliah ini membahas tentang PostgreSQL/PostGIS sebagai database spasial dan pengembangan aplikasi GIS yang ada seperti aplikasi GIS untuk masjid, kuliner, tanah dan penduduk.
Materi Pembelajaran/ Pokok Bahasan	Materi Ajar : PostGIS PostgreSQL Aplikasi GIS untuk masjid, kuliner, tanah dan penduduk
Pustaka	<p>Utama :</p> <ol style="list-style-type: none"> 1. PostgreSQL 2. PostGIS. 3. Aplikasi GIS untuk mesjid, kuliner, penduduk dan bangunan (Hasil riset) <p>Pendukung :</p> <ul style="list-style-type: none"> -
Media Pembelajaran	<p>Perangkat Lunak : Aplikasi GIS untuk mesjid, kuliner, penduduk dan bangunan</p> <p>Perangkat keras : Infocus</p>
Team Teaching	1. Prof. Surya Afnarius, PhD
Assessment	
Matakuliah Syarat	-

5

Mg-Ke-	Kemampuan akhir yg diharapkan	Bahan Kajian (Materi Ajar) Dan Referensi	Metode Pembelajaran dan Alokasi Waktu	Pengalaman Belajar Mahasiswa	Kriteria (Indikator) Penilaian	Bobot Penilaian (%)
(1)	(2)	(3)	(4)	(5)	(6)	(7)
1, 2,3,4	memahami basis data PostgreSQL /PostGIS untuk mengembangkan sistem informasi spasial (KU11, KK3)	PostgreSQL/PostGIS	Kuliah dan diskusi, (TM;4x(3x50'))	Mahasiswa membentuk kelompok dan mencari informasi dari berbagai sumber (terutama Internet).		
5,6,7	memahami sistem informasi spasial yang ada (P1, P2, KU2, KU10)	Aplikasi GIS untuk mesjid, kuliner, tanah dan penduduk	Kuliah dan diskusi, (TM;3x(3x50'')	Mahasiswa mengkaji jalanya aplikasi dan menambahkan fungsional tambahan.		
8	UTS/Tugas Besar				Adanya fungsional-fungsional tambahan untuk aplikasi GIS mesjid, kuliner, tanah atau penduduk.	20
9,10,11 .12,13, 14,15	mengembangkan sistem informasi spasial yang ada (S9, KU2,KU10, KU11, KK3)	Aplikasi GIS untuk mesjid, kuliner, tanah dan penduduk	Kuliah, diskusi, presentasi (TM;7x(3x50'')	Mahasiswa mengimplementasikan fungsional-fungsional tambahan aplikasi GIS mesjid, kuliner, tanah atau penduduk..	Fungsional-fungsional tambahan pada aplikasi GIS mesjid, kuliner, tanah atau penduduk telah diimplementasikan	80
16	UAS/Tugas Besar					

6

	PROGRAM STUDI : Sistem Informasi FAKULTAS /PPs: Teknologi Informasi UNIVERSITAS ANDALAS				
RENCANA TUGAS MAHASISWA					
MATA KULIAH Basis data lanjut					
KODE	TSI	skls	3	SEMESTER	5
DOSEN PENGAMPU	Prof. Surya Afnarius, PhD				
BENTUK TUGAS					
Final Project					
JUDUL TUGAS					
Tugas: Final Project: Mengembangkan aplikasi GIS yang ada dan mempresentasikan.					
SUB CAPAIAN PEMBELAJARAN MATA KULIAH					
- Mahasiswa mampu mengembangkan sistem informasi spasial yang ada					
DISKRIPSI TUGAS					
Mengembangkan sistem informasi spasial yang ada					
METODE PENGERJAAN TUGAS					
<ol style="list-style-type: none"> 1. Memilih satu SI spasial yang ada; 2. Mempelajari cara kerja SI spasial tsb; 3. Menghasilkan luaran SI; 4. Menyusun laporan; 5. Menyusun bahan & slide presentasi laporan; 6. Presentasi laporan di klas. 					
BENTUK DAN FORMAT LUARAN					
a. Obyek Garapan: satu SI spasial yang ada					
b. Bentuk Luaran:					
<ol style="list-style-type: none"> 1. Laporan ditulis dengan MS Word dengan sistematika dan format sesuai dengan standar panduan penulisan, dikumpulkan dengan format ekstensi (*.rtf), dengan sistematika nama file: (Tugas-laporan-no nrpmhs-nama depan mhs.rtf); 2. Slide Presentasi PowerPoint, terdiri dari : Text, grafik, tabel, gambar, animasi ataupun video clips, minimum 10 slide. Dikumpulkan dlm bentuk softcopyformat ekstensi (*.ppt), dengan sistematikan nama file: (Tugas-Slide-no nrpmhs-nama depan mhs.ppt); 					
INDIKATOR, KRETERIA DAN BOBOT PENILAIAN					
a. Laporan (50%)					
Fungsional-fungsional yang dikembangkan dan Kesesuaian data di dalam database dengan luaran yang dihasilkan.					
b. Penyusunan Slide Presentasi (bobot 20%)					
Jelas dan konsisten, Sedehana & inovative, menampilkan gambar & blok sistem, tulisan menggunakan font yang mudah dibaca, jika diperlukan didukung dengan gambar dan vedio clip yang relevant.					
c. Presentasi (bobot 30%)					
Bahasa komunikatif, penguasaan materi, penguasaan audiensi, pengendalian waktu (15 menit presentasi + 5 menit diskusi), kejelasan & ketajaman paparan, penguasaan media presentasi.					
JADWAL PELAKSANAAN					
Mengembangkan SI spasial yang ada	Minggu 1 s/d Minggu 11				
Menyusun laporan	Minggu 12 s/d Minggu 13				

Presentasi laporan Pengumuman nilai	Minggu 14 s/d 15 Dua minggu setelah UAS
LAIN-LAIN	
Bobot penilaian tugas ini adalah 100% dari penilaian mata kuliah ini; Tugas dikerjakan dan dipresentasikan secara kelompok;	
DAFTAR RUJUKAN	
- Aplikasi GIS untuk mesjid, kuliner, penduduk dan bangunan (Hasil riset)	

Minggu 1, 2, 3 dan 4

PostGreSQL/PostGIS

Bahan yang perlu dibaca sebagai persiapan diskusi dapat dilihat pada situs ini:

<http://www.postgresqltutorial.com/>

<http://workshops.boundlessgeo.com/postgis-intro/>

Selain itu, bahan dapat juga diambil dari :

<https://www.tutorialspoint.com/postgresql/index.htm>

http://www.bostongis.com/?content_name=postgisonline

<https://postgis.net/documentation/>

The screenshot shows the homepage of PostgreSQLTutorial.com. At the top, there's a navigation bar with links for HOME, STORED PROCEDURES, TRIGGERS, VIEWS, INTERFACES, and FUNCTIONS. Below the navigation is a search bar labeled "Search this website ...". The main content area has sections for "POSTGRESQL QUICK START" (links to What is PostgreSQL?, Install PostgreSQL, Connect to Database, Download PostgreSQL Sample Database, Load Sample Database, Explore Server and Database Objects), "POSTGRESQL FUNDAMENTALS" (links to SELECT, ORDER BY, SELECT DISTINCT, WHERE), and "If you are..." (links to Looking for learning PostgreSQL fast and easily, Developing applications using PostgreSQL as the back-end database management system, Migrating from other database management systems such as MySQL, Oracle, Microsoft SQL Server to PostgreSQL). A sidebar on the right lists various PostgreSQL features and highlights.

Materi minggu 1:

1. Getting started with PostgreSQL

- overview singkat tentang of PostgreSQL
- install PostgreSQL dan koneksi PostgreSQL database server dari psql atau pgAdmin.
- Download contoh database PostgreSQL dan masukkan ke dalam PostgreSQL database server

This screenshot shows a web browser displaying the "What is PostgreSQL?" page from PostgreSQLTutorial.com. The page content discusses PostgreSQL as a general-purpose and object-relational database management system, highlighting its portability across various platforms including Mac OS X, Solaris, and Windows. It also mentions PostgreSQL's status as free and open-source software.

This screenshot shows a web browser displaying the "PostgreSQL features highlights" page from PostgreSQLTutorial.com. The page lists several advanced features of PostgreSQL, such as its support for multiple inheritance, polymorphism, and triggers, which are not typically found in other enterprise database management systems.

This screenshot shows a web browser displaying the "Install PostgreSQL" page from PostgreSQLTutorial.com. The page instructs users to download the PostgreSQL installer for Windows from the official PostgreSQL website. It also provides a link to the PostgreSQL GitHub repository for the latest version.

This screenshot shows a web browser displaying the "Install PostgreSQL step by step" page from PostgreSQLTutorial.com. The page provides a visual guide for installing PostgreSQL on a Windows system, showing the file structure on the Local Disk (C) and the file "postgresql-9.5.0-1-windows-x64.exe". It also includes a note about the installation process for different PostgreSQL versions.

belajar postgresql - Penelusuran | PostgreSQL Tutorial - Learn PostgreSQL | PostgreSQL Sample Database | +

We will use the DVD rental database for demonstrating the features of PostgreSQL.

The DVD rental database was ported from the sakila sample database for PostgreSQL with some adjustments. The DVD rental database represents business processes of a DVD rental store. The DVD rental database has many objects including:

- 15 tables
- 1 trigger
- 7 views
- 8 functions
- 1 domain
- 13 sequences

DVD Rental ER Model

```

    graph LR
        category[category] --> inventory[inventory]
        category --> customer[customer]
        inventory --> customer
        inventory --> film[film]
        film --> customer
        film --> store[store]
        store --> customer
        store --> staff[staff]
        staff --> customer
        staff --> address[address]
        address --> customer
    
```

Activate Windows
Go to Settings to activate Windows 10

belajar postgresql - Penelusuran | PostgreSQL Tutorial - Learn PostgreSQL | PostgreSQL ORDER BY | +

Introduction to PostgreSQL ORDER BY clause

When you query data from a table, PostgreSQL returns the rows in the order that they were inserted into the table. In order to sort the result set, you use the ORDER BY clause in the SELECT statement.

The ORDER BY clause allows you to sort the rows returned from the SELECT statement in ascending or descending order based on the specified criteria.

The following illustrates the syntax of the ORDER BY clause:

```

1 SELECT
2   column_1,
3   column_2
4   FROM
5   tbl_name
6   ORDER BY
7     column_1 ASC,
8     column_2 DESC;

```

Let's examine the syntax of the ORDER BY clause in more detail:

- First, specify the column that you want to sort in the ORDER BY clause. If you sort the result set based on multiple columns, use a comma to separate between two columns.
- Second, use ASC to sort the result set in ascending order and DESC to sort the result set in descending order. If you leave it blank, the ORDER BY clause will use ASC by default.

Activate Windows
Go to Settings to activate Windows 10

2. Querying Data

Select

Order By

Select Distinct

belajar postgresql - Penelusuran | PostgreSQL Tutorial - Learn PostgreSQL | PostgreSQL SELECT | +

PostgreSQL SELECT statement syntax

Let's start with a basic form of the SELECT statement that retrieves data from a single table.

The following illustrates the syntax of the SELECT statement:

```

1 SELECT
2   column_1,
3   column_2,
4   ...
5   FROM
6   table_name;

```

Let's examine the SELECT statement in more detail:

- First, you specify the column of the table from which you want to query data in the SELECT clause. If you retrieve data from multiple columns, you use a comma to separate two columns. In case you want to query data from all columns, you can use an asterisk (*) as the shorthand.
- Second, you indicate the table name after the FROM keyword.

Note that the SQL language is case insensitive. It means that SELECT or select has the same effect. By convention, we will use SQL keywords in uppercase to make the code easier to read.

Activate Windows
Go to Settings to activate Windows 10

belajar postgresql - Penelusuran | PostgreSQL Tutorial - Learn PostgreSQL | PostgreSQL SELECT DISTINCT | +

Introduction to PostgreSQL SELECT DISTINCT clause

The DISTINCT clause is used in the SELECT statement to remove duplicate rows from the result set. The DISTINCT clause keeps one row for each group of duplicates. The DISTINCT clause can be used on one or more columns of a table.

The following illustrates the syntax of the DISTINCT clause:

```

1 SELECT
2   DISTINCT column_1,
3   column_2
4   FROM
5   table_name;

```

In this statement, the values in the column_1 column are used to evaluate the duplicate. If you specify multiple columns, the DISTINCT clause will evaluate the duplicate based on the combination of values of these columns.

```

1 SELECT
2   DISTINCT column_1,
3   column_2
4   FROM
5   tbl_name;

```

In this case, the combination of both column_1 and column_2 will be used for evaluating duplicate.

Activate Windows
Go to Settings to activate Windows 10

3. Filtering data

Where

Limit

Fetch

In

Between

Like

The screenshot shows a PostgreSQL WHERE clause tutorial page. It includes a code example for a WHERE clause and a table comparing standard comparison operators (=, >, <, >=) with their descriptions.

Operator	Description
=	Equal
>	Greater than
<	Less than
>=	Greater than or equal

The following table illustrates the standard comparison operators.

The screenshot shows a PostgreSQL LIMIT clause tutorial page. It includes a code example for a LIMIT clause and a note about using OFFSET to skip rows.

The screenshot shows a PostgreSQL IN operator tutorial page. It includes a code example for an IN clause and a note about nested queries.

The screenshot shows a PostgreSQL FETCH clause tutorial page. It includes a code example for a FETCH clause and notes on standard conformance.

The screenshot shows a PostgreSQL BETWEEN clause tutorial page. It includes a code example for a BETWEEN clause and notes on range filtering.

The screenshot shows a PostgreSQL LIKE clause tutorial page. It includes a code example for a LIKE clause and notes on pattern matching.

Introduction to the PostgreSQL BETWEEN operator

You use the `BETWEEN` operator to match a value against a range of values. The following illustrates the syntax of the `BETWEEN` operator:

```
1 value BETWEEN low AND high;
```

If the value is greater than or equal to the `low` value and less than or equal to the `high` value, the expression returns true, otherwise, it returns false.

You can rewrite the `BETWEEN` operator by using the greater than or equal (`>=`) or less than or equal (`=<`) operators as the following statement:

```
1 value >= low AND value <= high;
```

If you want to check if a value is out of a range, you combine the `NOT` operator with the `BETWEEN` operator as follows:

```
1 value NOT BETWEEN low AND high;
```

The following expression is equivalent to the expression that uses the `NOT` and `BETWEEN` operators:

```
1 value < low OR value > high;
```

Introduction to PostgreSQL LIKE operator

Suppose the store manager asks you find a customer that he does not remember the name exactly. He just remembers that customer's first name begins with something like `Jen`. How do you find the exact customer that the store manager is asking? You may find the customer in the `customer` table by looking at the first name column to see if there is any value that begins with `Jen`. It is kind of tedious because there many rows in the `customer` table.

Fortunately, you can use the PostgreSQL `LIKE` operator to as the following query:

```
1 SELECT
2   first_name,
3   last_name
4 FROM
5   customer
6 WHERE
7   first_name LIKE 'Jen%';
```

first_name	last_name
Jennifer	Devis
Jenny	Terry
Jenny	Castro

Notice that the `WHERE` clause contains a special expression: the `first_name`, the `LIKE` operator and a string that contains a percent (%) character, which is referred as a pattern.

4. Joining multiple tables

Inner Join.

Left Join.

Self-join

Full Outer Join

Cross Join

Natural Join

Introduction to PostgreSQL INNER JOIN clause

So far, you have learned how to select data from a table, choosing which columns and rows you want, and how to sort the result set in a particular order.

It is time to move to one of the most important concepts in the database called joining that allows you to relate data in one table to the data in other tables. There are several kinds of joins that include `INNER JOIN`, `OUTER JOIN` and self-join. This tutorial focuses on the `INNER JOIN`.

Suppose you want to get data from two tables named `A` and `B`. The `B` table has the `Eks` field that relates to the primary key of the `A` table.

To get data from both tables, you use the `INNER JOIN` clause in the `SELECT` statement as follows:

```
1 SELECT
2   A.pka,
3   A.c1,
4   B.pkb,
5   B.c2
6 FROM
7   A
8   INNER JOIN
9     B
10    ON A.pka = B.fa;
```

Introduction to PostgreSQL LEFT JOIN clause

Suppose we have two tables: `A` and `B`.

The data in the `B` table relates to the data in the `A` table via the `Eks` field.

Each row in the `A` table may have zero or many corresponding rows in the `B` table. Each row in the `B` table has one and only one corresponding row in the `A` table.

If you want to select rows from the `A` table that have corresponding rows in the `B` table, you use the `INNER JOIN` clause.

If you want to select rows from the `A` table which may or may not have corresponding rows in the `B` table, you use the `LEFT JOIN` clause. In case, there is no matching row in the `B` table, the values of the columns in the `B` table are substituted by the `NULL` values.

The following statement illustrates the `LEFT JOIN` syntax that join A table to B table:

```
1 SELECT
2   A.pka,
3   A.c1,
4   B.pb,
5   B.c2
6 FROM
7   A
8   LEFT JOIN
9     B
10    ON A.pka = B.fa;
```

www.postgresqltutorial.com/postgresql-self-join/

Introduction to PostgreSQL self-join

A self-join is a query in which a table is joined to itself. Self-joins are useful for comparing values in a column of rows within the same table.

To form a self-join, you specify the same table twice with different aliases, set up the comparison, and eliminate cases where a value would be equal to itself.

The following query shows how to join the table A to itself:

```
1 SELECT column_list
2 FROM A a1
3 INNER JOIN B b1 ON join_predicate;
```

In this syntax, table A is joined to itself using the `INNER JOIN` clause. Note that you can also use the `LEFT JOIN` or `RIGHT JOIN` clause.

PostgreSQL self-join examples

- 1) Querying hierarchy data example

Let's set up a sample table for the demonstration.

Suppose, we have the following organization structure:

www.postgresqltutorial.com/postgresql-cross-join/

Introduction to the PostgreSQL CROSS JOIN clause

A `CROSS JOIN` clause allows you to produce the Cartesian Product of rows in two or more tables. Different from the other JOIN operators such as `LEFT JOIN` or `INNER JOIN`, the `CROSS JOIN` does not have any matching condition in the join clause.

Suppose we have to perform the `CROSS JOIN` of two tables T1 and T2. For every row from T1 and T2 i.e., a cartesian product, the result set will contain a row that consists of all columns in the T1 table followed by all columns in the T2 table. If T1 has N rows, T2 has M rows, the result set will have $N \times M$ rows.

The following illustrates the syntax of the PostgreSQL CROSS JOIN clause:

```
1 SELECT *
2 FROM T1
3 CROSS JOIN T2;
```

The following statement is also equivalent to the CROSS JOIN above:

```
1 SELECT *
2 FROM T1, T2;
```

You can use the `INNER JOIN` clause with the condition evaluates to true to perform the cross join as follows:

www.postgresqltutorial.com/postgresql-full-outer-join/

Introduction to the PostgreSQL FULL OUTER JOIN

Suppose, you want to perform a full outer join of two tables: A and B. The following illustrates the syntax of the FULL OUTER JOIN:

```
1 SELECT * FROM A
2 FULL [OUTER] JOIN B on A.id = B.id;
```

The `OUTER` keyword is optional.

The full outer join combines the results of both `left join` and `right join`. If the rows in the joined table do not match, the full outer join sets NULL values for every column of the table that lacks a matching row. For the matching rows, a single row is included in the result set that contains columns populated from both joined tables.

The following Venn diagram illustrates the FULL OUTER JOIN operation:

Activate Windows
Go to Settings to activate Windows 10

www.postgresqltutorial.com/postgresql-natural-join/

A natural join is a join that creates an implicit join based on the same column names in the joined tables.

See the following syntax of PostgreSQL natural join:

```
1 SELECT *
2 FROM T1
3 NATURAL [INNER, LEFT, RIGHT] JOIN T2;
```

A natural join can be an `inner join`, `left join`, or `right join`. If you do not specify a join explicitly e.g., `INNER JOIN`, `LEFT JOIN`, `RIGHT JOIN`, PostgreSQL will use the `INNER JOIN` by default.

If you use the asterisk (*) in the select list, the result will contain the following columns:

- All the common columns, which are the columns in the both tables that have the same name
- Every column in the first and second tables that is not a common column

PostgreSQL NATURAL JOIN examples

To demonstrate the PostgreSQL natural join, we will create two tables: `categories` and `products`. The following `CREATE TABLE` statements create the `categories` and `products` table.


```
1 CREATE TABLE categories (
2   category_id serial PRIMARY KEY,
3   category_name VARCHAR (255) NOT NULL
4 );
```

PROGRAM APLIKASI GIS KULINER KHAS BUKITTINGGI

PROGRAM APLIKASI GIS KULINER KHAS BUKITTINGGI



Ada 6 (enam) modul program/ fitur/ fungsional, yaitu modul program untuk:

1. Mencari tempat kuliner berdasarkan jenis kuliner
 2. Mencari tempat kuliner berdasarkan fasilitas
 3. Menampilkan detail informasi tempat kuliner
 4. Menampilkan galeri tempat kuliner
 5. Menampilkan pariwisata (objek wisata, hotel, restoran, kuliner, industri kecil, dan souvenir) yang berada disekitaran tempat kuliner
 6. Menampilkan informasi detail pariwisata



SURYA AFNARIUS DAN FITRIANY CHAIRUNNISA
SISTEM INFORMASI
UNIVERSITAS ANDALAS

Usecase diagram aplikasi GIS kuliner khas Bukittinggi



Ada enam modul program, yaitu:

1. Mencari tempat kuliner berdasarkan jenis kuliner

a. Use case scenario

Table 1. Skenario Mencari Tempat Kuliner Berdasarkan Jenis Kuliner

<i>Use case name</i>	Mencari Tempat Kuliner Berdasarkan Jenis Kuliner
<i>Participating Actor</i>	User
<i>Flow Of Events</i>	1. User memilih pada menu sidebar button view culinary
	2. User memilih select culinary pada sub menu button view culinary
	3. User memilih jenis kuliner yang tersedia dalam bentuk checkbox
	4. User menekan button search
	5. Sistem menampilkan posisi dan daftar tempat kuliner yang dicari
<i>Exit Condition</i>	User dapat melihat tempat kuliner berdasarkan jenis kuliner
<i>Alternative Course</i>	1. User memilih pada menu sidebar button view culinary
	2. User memilih select culinary pada sub menu button view culinary
	3. User memilih jenis kuliner yang tersedia dalam bentuk checkbox
	4. User menekan button search
	5. Sistem akan menampilkan "Data Didn't Exist!"

b. Code

- Javascript

```
function viewkul(){
{
    clearroute2();
    $("#hasilik").show();
    $("#hasilcaril").show();
    $("#hasilcari").empty();
    $("#hasilcari").empty();
```

```
$('#hasilpencarian').empty();

hapusInfo();
hapusMarkerTerdekat();
var fas=selectkul.value;
var arrayLay=[];
for(i=0;i<$("input[name=culinary]:checked").length;i++){
    arrayLay.push($(".input[name=culinary]:checked")[i].value);
} //Perulangan saat memilih checkbox
console.log('zz');
if (arrayLay==''){
    alert('Pilih Kuliner');
}else{
    $('#hasilcari').append("<thead><th>Name</th><th
    colspan='3'>Action</th></thead>");
$.ajax({ url: server+'selectkul.php?lay='+arrayLay, data: "", dataType: 'json', success: function(rows) {
    console.log("hai");
    if(rows==null)//Jika tidak ada data
    {
        alert('Data not found');
    }
    for (var i in rows)
    {
        var row      = rows[i];
        var id       = row.id;
        var nama_kuliner = row.name;
        var nama_tempat_kuliner = row.name;
        var latitude = row.latitude ;
        var longitude = row.longitude ;
        centerBaru   = new google.maps.LatLng(latitude,
longitude);
        marker = new google.maps.Marker
        ({
            position: centerBaru,
            icon:'assets/img/cul.png',
            map: map,
            animation: google.maps.Animation.DROP,
        });
        console.log(name);
        console.log(latitude);
        console.log(longitude);
        markersDua.push(marker);
        map.setCenter(centerBaru);
        map.setZoom(16);
        clickMarker(centerBaru, id);


        $('#hasilcari').append("<tr><td>"+nama_tempat_kuliner+"</t
d><td><a role='button' class='btn btn-success'
onclick='detculi(\""+id+"\")';detailinfokul(\""+id+"\");'>S
how</a></td><td><a role='button' class='btn btn-danger fa
fa-taxi' onclick='kulAngkot(\""+id+"\")'></a></td></tr>");
    }
    $('#hasilpencarian').append("<h5      class='box-title'
id='hasilpencarian'>Result :</h5>"+rows.length);
    }});
}
}
```

- [selectcul.php](#)

```
<?php
require 'connect.php';

$lay=$_GET['lay'];
$lay = explode(", ", $lay);
$c = "";
for($i=0;$i<count($lay);$i++) { //Perulangan saat memilih checkbox
    if($i == count($lay)-1){
        $c .= "'".$lay[$i]."'";
    }else{
        $c .= "'".$lay[$i]."',";
    }
}
$querysearch="select
culinary_place.id,culinary_place.name,ST_X(ST_Centroid(culinary_place.geom)) AS lng, ST_Y(ST_CENTROID(culinary_place.geom)) AS lat
from culinary_place join detail_culinary on
culinary_place.id=detail_culinary.id_culinary_place where
detail_culinary.id_culinary in ($c) group by id";
$hasil=pg_query($querysearch);
while($row = pg_fetch_array($hasil))
{
    $id=$row['id'];
    $name=$row['name'];
    $longitude=$row['lng'];
    $latitude=$row['lat'];
    $dataarray[] = array('id'=>$id,'name'=>$name,'longitude'=>$longitude,'latitude'=>$latitude);
}
echo json_encode ($dataarray);
?>
```

c. Contoh luaran program



Memilih Jenis Kuliner dalam Checkbox

Tempat Kuliner Berdasarkan Jenis Kuliner

2. Mencari tempat kuliner berdasarkan fasilitas

a. Use case scenario

Tabel 2. Skenario Mencari Tempat Kuliner Berdasarkan Fasilitas

<i>Use case name</i>	Mencari Tempat Kuliner Berdasarkan Fasilitas
<i>Participating Actor</i>	User
<i>Flow Of Events</i>	<ol style="list-style-type: none"> 1. User memilih pada menu sidebar button <i>view culinary</i> 2. User memilih <i>facility</i> pada sub menu button <i>view culinary</i> 3. User memilih jenis fasilitas yang tersedia dalam bentuk <i>checkbox</i> 4. User menekan button <i>search</i> 5. Sistem menampilkan posisi dan daftar tempat kuliner yang dicari
<i>Exit Condition</i>	User dapat melihat tempat kuliner berdasarkan jenis kuliner
<i>Alternative Course</i>	<ol style="list-style-type: none"> 6. User memilih pada menu sidebar button <i>view culinary</i>

7. User memilih <i>facility</i> pada sub menu <i>button view culinary</i>
8. User memilih jenis fasilitas yang tersedia dalam bentuk <i>checkbox</i>
9. User menekan <i>button search</i>
10. Sistem akan menampilkan "Data Didn't Exist!"

b. Code

- Javascript

```
function viewfas()
{
    clearroute2();
    $("#hasilik").show();
    $('#hasilcari1').show();
    $('#hasilcari').empty();
    $('#hasilcari').empty();
    $('#hasilpencarian').empty();
    hapusInfo();
    hapusMarkerTerdekat();
    var fas=selectfacility.value;
    var arrayLay=[];
    for(i=0;i<$("input[name=facility]:checked").length;i++){
        arrayLay.push($("input[name=facility]:checked")[i].value);
    } //Perulangan saat memilih checkbox
    console.log(arrayLay);
    if (arrayLay=='') { //Jika Fasilitas Kosong
        alert('Pilih Fasilitas');
    }else{
        $('#hasilcari').append("<thead><th>Name</th><th>Action</th></thead>");
        $.ajax({ url: server+'selectfas.php?lay='+arrayLay, data: "", dataType: 'json', success: function(rows){
            console.log("hai");
            if(rows==null) //Jika Data Kosong
            {
                alert('Data not found');
            }
            for (var i in rows)
            {
                var row = rows[i];
                var id = row.id;
                var id_facility = row.id;
                var name_facility = row.name;
                var nama_tempat_kuliner = row.name;
                var latitude = row.latitude ;
                var longitude = row.longitude ;
                centerBaru = new google.maps.LatLng(latitude, longitude);
                marker = new google.maps.Marker
                ({
                    position: centerBaru,
                    icon:'assets/img/cul.png',

```

```
map: map,
animation: google.maps.Animation.DROP,
});
console.log(name);
console.log(latitude);
console.log(longitude);
markersDua.push(marker);
map.setCenter(centerBaru);
map.setZoom(12);
clickMarker(centerBaru, id);

$('#hasilcari').append("<tr><td>"+nama_tempat_kuliner+"</td><td><a role='button' class='btn btn-success' onclick='detculi(\""+id+"\")';detailinfokul(\""+id+"\");'>Show</a></td><td><a role='button' class='btn btn-danger fa fa-taxi' onclick='kulAngkot(\""+id_facility+"\")'></a></td></tr>");
}
$('#hasilpencarian').append("<h5 class='box-title' id='hasilpencarian'>Result :</h5>"+rows.length);
})
}
}



```

- *selectfas.php*


```
<?php
require 'connect.php';
$lay=$_GET['lay'];
$lay = explode(", ", $lay);
$c = "";
for($i=0;$i<count($lay);$i++){
    if($i == count($lay)-1){
        $c .= "'".$lay[$i]."'";
    }else{
        $c .= "'".$lay[$i]."',";
    }
}
$querysearch="select
culinary_place.id,culinary_place.name,ST_X(ST_Centroid(culinary_place.geom)) AS lng, ST_Y(ST_CENTROID(culinary_place.geom)) As lat from
culinary_place join detail_facility_culinary on
culinary_place.id=detail_facility_culinary.id_culinary_place where
detail_facility_culinary.id_facility in ($c) group by id";
$hasil=pg_query($querysearch);
while($row = pg_fetch_array($hasil))
{
    $id=$row['id'];
    $id_facility=$row['id'];
    $name=$row['name'];
    //$name=$row['name'];
    $longitude=$row['lng'];
    $latitude=$row['lat'];

    $dataarray[] = array('id'=>$id,'id_facility'=>$id,'name'=>$name,'longitude'=>$longitude,'latitude'=>$latitude);
}
echo json_encode ($dataarray);
?>
```

c. Contoh luaran program



Memilih Fasilitas dalam Checkbox



Tempat Kuliner Berdasarkan Fasilitas

3. Menampilkan Detail Informasi Tempat Kuliner

a. Use case scenario

Tabel 3. Skenario Menampilkan Detail Informasi Tempat Kuliner

<i>Use case name</i>	Menampilkan Detail Informasi Tempat Kuliner
<i>Participating Actor</i>	<i>User</i>
<i>Flow Of Events</i>	<ol style="list-style-type: none"> 1. <i>User</i> menekan button <i>show</i> pada list tempat kuliner yang diinginkan 2. Sistem menampilkan detail tempat kuliner yang dipilih
<i>Exit Condition</i>	<i>User</i> dapat melihat detail informasi tempat kuliner yang dipilih

b. Code

- Javascript

```
function detailinfokul(id144)
{
  $('#info').empty();
  $('#hasilcaridetculi').empty();
  $('#hasilcaridetculi').show();
  $('#hasildet').show();
  $('#hasilcaridet').empty();
  $('#hasilcaridet1').show();
  hapusInfo();
  $.ajax({
    url: server+'detailinfokul.php?info=' + id144, data: "", dataType: 'json',
    success: function(rows)
    {
      for (var i in rows) //Perulangan menampilkan data
      {
        console.log('ddd');
        var row = rows[i];
        var id = row.id;
        var namaa = row.name;
        var capacity = row.capacity;
        var address=row.address;
        var cp=row.cp;
        var open = row.open;
        var close = row.close;
        var fasilitas = row.fasilitas;
        var latitude = row.latitude;
        var longitude = row.longitude;
        centerBaru = new google.maps.LatLng(row.latitude, row.longitude);
        marker = new google.maps.Marker
        ({
          position: centerBaru,
          icon:'assets/img/cul.png',
          map: map,
          animation: google.maps.Animation.DROP,
        })
        var infowindow = new google.maps.InfoWindow
        ({
          content: "Name : "+namaa+
          "  
Capacity : "+capacity+
          "  
Address : "+address+
          "  
Phone : "+cp+
          "  
Open : "+open+
          "  
Close : "+close+
          "  
Fasilitas : "+fasilitas+
          "  
Latitude : "+latitude+
          "  
Longitude : "+longitude
        })
        marker.addListener('click', function()
        {
          infowindow.open(map,marker);
        })
      }
    }
  })
}
```

```

        });
        console.log(latitude);
        console.log(longitude);
        markersDua.push(marker);
        map.setCenter(centerBaru);
        map.setZoom(18);
    <br> Kapasitas : "+kapasitas+" );
    }
};

function detculi(id14433){
    $('#info').empty();
    $('#hasilcaridetculi').empty();
    $('#hasilcaridetculi1').show();
    $('#hasildet').show();
    $('#hasilcaridet').empty();
    $('#hasilcaridet1').show();
    hapusInfo();
    $.ajax({
        url: server+'detculi.php?info='+id14433, data: "", dataType: 'json', success: function(rows)
        {
            $('#hasilcaridet').append("<tr><td colspan='2'><strong>Culinary</strong></td><td><strong>Price</strong></td></tr>");
            for (var i in rows) //Perulangan menampilkan data
            {
                var row = rows[i];
                var id = row.id;
                var nama = row.name;
                var capacity = row.capacity;
                var address=row.address;
                var cp=row.cp;
                var open=row.open;
                var close=row.close;
                var price = row.price;
                var culinary = row.culinary;
                var latitude = row.latitude;
                var longitude = row.longitude;
                centerBaru = new google.maps.LatLng(row.latitude, row.longitude);
                marker = new google.maps.Marker
                ({
                    position: centerBaru,
                    icon:'assets/img/cul.png',
                    map: map,
                    animation: google.maps.Animation.DROP,
                });
                console.log(latitude);
                console.log(longitude);
                console.log(id);
                markersDua.push(marker);
                map.setCenter(centerBaru);
                map.setZoom(18);
            }
        });
    }
}

function hapusInfo()
{
    $('#info').empty();
}

```

```

        infowindow = new google.maps.InfoWindow({
            position: centerBaru,
            content: "<center><span style='color:black'><b>Information</b></span><table><tr><td><i class='fa fa-home'></i>Nama</td><td></td></tr><br><tr><td><i class='fa fa-map-marker'></i>Alamat</td><td></td></tr><br><tr><td><i class='fa fa-phone'></i>Telepon</td><td></td></tr><br><tr><td><i class='fa fa-clock-o'></i>Open</td><td></td></tr><br><tr><td><i class='fa fa-clock-o'></i>Close</td><td></td></tr><br><tr><td><i class='fa fa-building'></i>Capacity</td><td></td></tr><br><tr><td><i class='fa fa-clock-o'></i>+capacity</td><td></td></tr></table></span><br><input type='button' class='btn btn-success' value='Object Arround' onclick='tampil_sekitar(\""+latitude+"\",\""+longitude+"\",""+namaa+"\")'><br>&nbsp;&nbsp;<input type='button' class='btn btn-success' value='Gallery' onclick='gallery(\""+id+"\")'><br>&nbsp;&nbsp; <input type='button' class='btn btn-success' value='Route' onclick='callRoute(centerLokasi,centerBaru);ruteTampil()' />", pixelOffset: new google.maps.Size(0, -33));
            });
            infoposisi.push(infowindow);
            hapusInfo();
            infowindow.open(map);
        }
    });
}

```

- [detailinfokul.php](#)

```

<?php
require 'connect.php';
$info = $_GET["info"];
$querysearch = "select
culinary_place.id,culinary_place.name,culinary_place.capacity,culinary_place.address,culinary_place.cp,culinary_place.open,culinary_place.close,
newtable.id_culinary_place,ST_X(ST_Centroid(culinary_place.geom)) AS lng,
ST_Y(ST_CENTROID(culinary_place.geom)) AS lat, newtable.fasilitas from
(select
detail_facility_culinary.id_culinary,
string_agg(facility_culinary.facility, ',') as fasilitas
from detail_facility_culinary join facility_culinary on facility_culinary.id = detail_facility_culinary.id_facility
where detail_facility_culinary.id_culinary_place='$info' group by
detail_facility_culinary.id_culinary_place) as newtable join
culinary_place on culinary_place.id = newtable.id_culinary_place";
//Menampilkan data untuk detail informasi

$hasil=pg_query($querysearch);
while($row = pg_fetch_array($hasil)) //Perulangan menampilkan data
{
    $id=$row['id'];

```

```

$name=$row['name'];
$capacity=$row['capacity'];
$address=$row['address'];
$cp=$row['cp'];
$open=$row['open'];
$close=$row['close'];
$fasilitas=$row['fasilitas'];
$longitude=$row['lng'];
$latitude=$row['lat'];

```

```

$dataarray[] = array('id'=>$id, 'name'=>$name, 'capacity'=>$capacity, 'address'=>$address, 'cp'=>$cp, 'close'=>$close, 'fasilitas'=>$fasilitas, 'open'=>$open, 'longitude'=>$longitude, 'latitude'=>$latitude);
}
echo json_encode ($dataarray);
?>

```

- **detculi.php**

```

<?php
require 'connect.php';
$info = $_GET["info"];

$querysearch
          ="select
culinary_place.id, culinary_place.name, culinary_place.capacity, culinary_place.address, culinary_place.cp, culinary_place.open, culinary_place.close,
newtable.id_culinary_place, newtable.price, ST_X(ST_Centroid(culinary_place.geom))    As  lat,
newtable.culinary
          from
          (select
detail_culinary.id_culinary_place, detail_culinary.price,
string_agg(culinary.name, ', ') as culinary from detail_culinary join
culinary
          on
          culinary.id
          =
          detail_culinary.id_culinary
          where
          detail_culinary.id_culinary_place=' $info '
          group
          by
          detail_culinary.id_culinary_place, detail_culinary.price) as newtable
join
culinary_place on culinary_place.id = newtable.id_culinary_place";
//Menampilkan data untuk detail informasi

$hasil=pg_query($querysearch);
while($row = pg_fetch_array($hasil)) //Perulangan menampilkan data
{
    $id=$row['id'];
    $name=$row['name'];
    $capacity=$row['capacity'];
    $address=$row['address'];
    $cp=$row['cp'];
    $open=$row['open'];
    $close=$row['close'];
    $price=$row['price'];
    $culinary=$row['culinary'];
    $longitude=$row['lng'];
    $latitude=$row['lat'];

$dataarray[] = array('id'=>$id, 'name'=>$name, 'capacity'=>$capacity, 'address'=>$address, 'cp'=>$cp, 'open'=>$open, 'close'=>$close, 'culinary'=>$culinary, 'price'=>$price, 'longitude'=>$longitude, 'latitude'=>$latitude);
}


```

```

echo json_encode ($dataarray);
?>

```

c. Contoh luaran program



Detail informasi tempat kuliner yang dipilih

4. Menampilkan Gallery Foto

a. Use case scenario

Tabel 4. Skenario Menampilkan Gallery Foto

Use case name	Menampilkan Gallery Foto
Participating Actor	User
Flow Of Events	<ol style="list-style-type: none"> 1. User menekan button show pada objek yang dipilih 2. Sistem menampilkan detail informasi objek yang dipilih 3. User menekan button gallery pada objek yang dipilih 4. Sistem menampilkan gallery foto objek yang dipilih
Exit Condition	User dapat melihat gallery foto

b. Code

- Javascript

```
function gallery(azz){
    console.log(azz);
    window.open(server+'gallery.php?idgallery='+azz);
}
```


- **gallery.php**

```
<?php
    require 'connect.php';

    $id = $_GET["idgallery"];

    $querysearch = " SELECT a.id, b.gallery_culinary as foto
                    FROM culinary_place as a left join
                    culinary_gallery as b on a.id=b.id where a.id='\$id' "; //Menampilkan foto
    echo "zzz";
    $hasil=pg_query($querysearch);
    while($baris = pg_fetch_assoc($hasil)) //Perulangan
menampilkan foto
    {
        if(($baris['foto']=='-' || ($baris['foto']=='')) //Jika foto tidak ada dalam database
        {
            echo "<a href='img/noimage.jpg'><img src='img/noimage.jpg' ></a>";
        }
        else//Jika foto ada dalam database
        {
            echo "<a href='img/".$baris['foto']."'><img src='img/".$baris['foto']."' ></a>";
        }
    } ?>
```

c. Contoh luaran program



Gallery Tempat Kuliner

5. Melihat pariwisata (objek wisata, hotel, restoran, kuliner, industri kecil, dan souvenir) yang berada disekitaran tempat kuliner yang dipilih

a. Use case scenario

Tabel 5. Skenario Mencari Souvenir Sekitar dengan Tempat Kuliner

<i>Use case name</i>	Mencari Hotel, Objek Wisata, Masjid, Industri Kecil, dan Souvenir Sekitar dengan Tempat Kuliner
<i>Participating Actor</i>	<i>User</i>
<i>Flow Of Events</i>	<ol style="list-style-type: none"> 1. <i>User</i> menekan button <i>show</i> pada list tempat kuliner yang diinginkan 2. Sistem menampilkan detail tempat kuliner yang dipilih 3. <i>User</i> menekan button <i>object arround</i> pada info window 4. Sistem menampilkan pilihan objek dalam bentuk <i>checkbox</i> dan radius dalam bentuk <i>seekbar</i> 5. <i>User</i> memilih objek dan radius yang diinginkan 6. Sistem menampilkan posisi dan list objek yang dipilih
<i>Exit Condition</i>	<i>User</i> dapat melihat hotel, objek wisata, masjid, industri kecil, dan souvenir sekitar dengan tempat kuliner sesuai dengan objek dan radius yang dipilih

b. Code

- Javascript

```
function oleholeh_sekitar(latitude,longitude,rad){ // OLEH-OLEH SEKITAR
    $('#hasilcarisouv').empty();
    $('#hasilcarisouv1').show();
    $('#hasilcarisouv').append("<thead><th colspan='3' class='centered'>Nama</th><th class='centered'>Aksi</th></thead>");
    $.ajax({url:server+'_sekitar_oleholeh.php?lat='+latitude+'&long='+longitude+'&ad='+rad, data: "", dataType: 'json', success: function(rows){
        for (var i in rows){ //Perulangan menampilkan data
            var row = rows[i];
            var id = row.id;
            var name = row.name;
            var owner = row.owner;
            var cp = row.cp;
```

```

var address = row.address;
var lat=row.latitude;
var lon = row.longitude;

//POSISI MAP
centerBaru = new google.maps.LatLng(lat, lon);
map.setCenter(centerBaru);
map.setZoom(16);
var marker = new google.maps.Marker({
  position: centerBaru,
  icon:'assets/img/souv.png',
  animation: google.maps.Animation.DROP,
  map: map
});
markersDua.push(marker);
map.setCenter(centerBaru);

$('#hasilcarisouv').append("<tr><td>"+name+"</td><td><a role='button' class='btn btn-danger fa fa-info' onclick='detailinfosou('"+id+"')'></a></td><td><a role='button' class='btn btn-danger fa fa-road' onclick='route_sekitar('"+latitude+"','"+longitude+"','"+lat+"','"+lon+"')'></a></td><td><a role='button' class='btn btn-danger fa fa-taxi' onclick='souangkot('"+id+"')'></a></td></tr>");
  //end for
}); //end ajax
}

```

- [_sekitar_oleholeh.php](#)

```

<?php

include('connect.php');
$latit = $_GET['lat'];
$longi = $_GET['long'];
$rad=$_GET['rad'];

$querysearch="SELECT id, name, owner, cp, address,
st_x(st_centroid(geom)) as lng, st_y(st_centroid(geom)) as lat,
st_distance_sphere(ST_GeomFromText('POINT(\".$longi.\" \"$._latit.\")',-1),
geom) as jarak FROM souvenir where
st_distance_sphere(ST_GeomFromText('POINT(\".$longi.\" \"$._latit.\")',-1),
geom) <= ".$rad.""; //Menampilkan data oleh-oleh sesuai radius yang dipilih

$hasil=pg_query($querysearch);

while($baris = pg_fetch_array($hasil)) //Perulangan menampilkan data
{
  $id=$baris['id'];
  $name=$baris['name'];
  $owner=$baris['owner'];
  $cp=$baris['cp'];
  $address=$baris['address'];

  $latitude=$baris['lat'];
  $longitude=$baris['lng'];

$dataarray[] = array('id'=>$id, 'name'=>$name, 'cp'=>$cp, 'address'=>$address,
"latitude"=>$latitude, "longitude"=>$longitude);
}


```

```

        }
echo json_encode ($dataarray);
?>

```

c. Contoh luaran program



Pariwisata (objek wisata, hotel, restoran, kuliner, industri kecil, dan souvenir) yang berada disekitaran tempat kuliner yang dipilih

6. Melihat informasi detail pariwisata yang dipilih

a. Use case scenario

Tabel 6. Skenario Menampilkan Detail Informasi Souvenir Sekitar Tempat Kuliner

<i>Use case name</i>	Menampilkan Detail Informasi Hotel, Objek Wisata, Masjid, Industri Kecil, dan Souvenir Sekitar Tempat Kuliner
<i>Participating Actor</i>	User
<i>Flow Of Events</i>	<ol style="list-style-type: none"> 1. User menekan button <i>object arround</i> pada info window 2. Sistem menampilkan pilihan objek dalam bentuk <i>checkbox</i> dan radius dalam bentuk <i>seekbar</i> 3. User memilih objek dan radius yang diinginkan 4. Sistem menampilkan posisi dan list objek yang dipilih 5. User menekan button <i>show</i> pada objek yang dipilih

	6. Sistem menampilkan detail informasi objek yang dipilih
<i>Exit Condition</i>	<i>User</i> dapat melihat detail informasi hotel, objek wisata, masjid, industri kecil, dan souvenir sekitar dengan tempat kuliner sesuai dengan objek yang dipilih

b. Code

- Javascript

```

function detailinfosou(id14)
{
    $('#info').empty();
    hapusInfo();
    // clearroute2();
    hapusMarkerTerdekat();
    $.ajax({
        url: server+'detailinfosou.php?info='+id14,      data:      "",
        dataType: 'json', success: function(rows)
        {
            for (var i in rows) //Perulangan menampilkan data
            {
                console.log('ddd');
                var row = rows[i];
                var id = row.id;
                var namaa = row.name;
                var address=row.address;
                var cp = row.cp;
                var owner = row.owner;

                var latitude = row.latitude; ;
                var longitude = row.longitude ;
                centerBaru = new google.maps.LatLng(row.latitude,
row.longitude);
                marker = new google.maps.Marker
                ({
                    position: centerBaru,
                    icon:'assets/img/souv.png',
                    map: map,
                    animation: google.maps.Animation.DROP,
                });
                console.log(latitude);
                console.log(longitude);
                markersDua.push(marker);
                map.setCenter(centerBaru);
                map.setZoom(18);
                if (address==null)
                {
                    address="tidak ada";
                }
            }
        }
    })
}

```


```
        }
        infowindow = new google.maps.InfoWindow({
            position: centerBaru,
            content: "<center><span style=color:black><b>Information</b><table><tr><td><i class='fa fa-home'></i>Nama</td><td>:</td><td>" + namaa + "</td></tr><br><tr><td><i class='fa fa-map-marker'></i>Alamat</td><td>:</td><td>" + address + "</td></tr><br><tr><td><i class='fa fa-phone'></i>Telepon</td><td>:</td><td>" + cp + "</td></tr></table></span>",
            pixelOffset: new google.maps.Size(0, -33)
        });
        infoposisi.push(infowindow);
        hapusInfo();
        infowindow.open(map);
    }
});
```

- detailinfosou.php

```
<?php
require 'connect.php';
$info = $_GET["info"];
$querysearch = "select id, name, owner, address, cp, ST_X(ST_Centroid(geom)) AS lng, ST_Y(ST_CENTROID(geom)) AS lat from souvenir where id='$info'";
    //Menampilkan data souvenir untuk detail informasi
$hasil=pg_query($querysearch);
while($row = pg_fetch_array($hasil)) //Perulangan menampilkan data
{
    $id=$row['id'];
    $name=$row['name'];
    $address=$row['address'];
    $cp=$row['cp'];
    $owner=$row['owner'];
    $longitude=$row['lng'];
    $latitude=$row['lat'];

$dataarray[] = array('id'=>$id, 'name'=>$name, 'address'=>$address, 'owner'=>$owner, 'cp'=>$cp, 'longitude'=>$longitude, 'latitude'=>$latitude);
}
echo json_encode ($dataarray);
?>
```

c. Contoh luaran program



Informasi detail pariwisata yang dipilih

PROGRAM APLIKASI GIS MONITORING TANAH DAN KEPENDUDUKAN NAGARI PADANG LUA


SURYA AFNARIUS DAN ANGGI TAMARA
SISTEM INFORMASI
UNIVERSITAS ANDALAS

PROGRAM APLIKASI GIS MONITORING TANAH DAN KEPENDUDUKAN NAGARI PADANG LUA

Ada 12 (Dua Belas) modul program/ fitur/ fungsional, yaitu modul program untuk :

1. Pencarian kapling tanah berdasarkan nomor objek pajak
2. Menampilkan list tanah
3. Mengelola data land history
4. Pencarian data bangunan berdasarkan nomor bangunan
5. Menampilkan list bangunan
6. Mengelola data building history
7. Pencarian kepemilikan tanah berdasarkan nomor penduduk
8. Pencarian data kepemilikan bangunan berdasarkan nomor penduduk
9. Pencarian data penduduk berdasarkan nomor penduduk
10. Mengelola data kelahiran
11. Mengelola data kematian
12. Mengelola data perpindahan

Use case diagram Aplikasi GIS Monitoring Tanah dan Kependudukan Nagari Padang Luu



Dua Belas modul program:

1. Pencarian Kapling Tanah Berdasarkan Nomor Objek Pajak

a. Use Case Scenario

Tabel 1. Prosedur Pencarian Kapling Tanah Berupa Informasi Teks

<i>Use case name</i>	Pencarian kapling tanah berupa informasi teks
<i>Participating Actor</i>	<i>User</i>
<i>Flow Of Events</i>	1. <i>User</i> memilih menu <i>land</i>
	2. Sistem akan menampilkan sub menu
	3. <i>User</i> memilih menu <i>land search</i>
	4. Sistem akan menampilkan menu <i>land search</i>
	2. <i>User</i> memasukan nomor objek pajak
	3. Sistem akan menampilkan informasi teks mengenai kapling tanah
<i>Entry condition</i>	<i>User</i> telah login
<i>Exit Condition</i>	<i>User</i> dapat melihat informasi teks mengenai kapling tanah yang diinginkan
<i>Alternative Course</i>	1. <i>User</i> memilih menu <i>land</i>
	2. Sistem akan menampilkan sub menu
	3. <i>User</i> memilih menu <i>land search</i>
	4. Sistem akan menampilkan menu <i>land search</i>
	4. <i>User</i> memasukan nomor objek pajak
	5. Sistem akan menampilkan "Data Not Found"

Tabel 2. Prosedur Pencarian Kapling Tanah Berupa Peta

<i>Use case name</i>	Pencarian kapling tanah berupa peta
<i>Participating Actor</i>	<i>User</i>
<i>Flow Of Events</i>	1. <i>User</i> memilih menu <i>land</i>
	2. Sistem akan menampilkan sub menu
	3. <i>User</i> memilih menu <i>land search</i>

	4. Sistem akan menampilkan menu <i>land search</i>
	5. <i>User</i> memasukan nomor objek pajak
	6. Sistem akan menampilkan data objek pajak
	7. <i>User</i> memilih tab <i>map</i>
	6. Sistem akan menampilkan lokasi berdasarkan nomor objek pajak yang diinputkan
<i>Entry condition</i>	<i>User</i> telah login
<i>Exit Condition</i>	<i>User</i> dapat melihat lokasi kapling tanah

b. Kode Program

```
// Pencarian Kapling Tanah Berdasarkan No Objek Pajak Berupa Informasi Teks
// Method untuk memanggil data dari database menggunakan bahasa
// pemrograman php
public function find_object($id){
// query berdasarkan pencarian tanah
$sql = "SELECT la.nop, la.high_property, la.pawning,
la.tax_value, la.land_size,
la.building_size,la.id_building,p.pemilik_id,c.name as
pemilikrumah,lp.NIK , jo.name AS address
FROM land AS la
left join \"pemilikRumah\" p ON p.id_building=la.id_building
left join land_proprietary lp on lp.nop=la.nop
left join citizen c on (c.NIK=p.pemilik_id) , jorong AS jo
WHERE ST_CONTAINS(jo.geom, ST_CENTROID(la.geom)) AND la.nop =
'$id'";
$Query = pg_Query($sql);
if(pg_num_rows($Query) > 0){
//generate hasil Query (informasi dari tanah)
$result = pg_fetch_assoc($Query);
$data['nop'] = $result['nop'];
$data['high_property'] = $result['high_property'];
$data['pawning'] = $result['pawning'];
$data['tax_value'] = $result['tax_value'];
$data['land_size'] = $result['land_size'];
$data['building_size'] = $result['building_size'];
$data['address'] = $result['address'];
$data['owner_rumah'] = $result['pemilikrumah'];
}
}
```

```
//Query memilih pemilik tanah
```

```
$sql = "SELECT ci.NIK, ci.name AS name, cs.name AS status,
EXTRACT(YEAR FROM AGE(ci.born_date)) AS age FROM land_proprietary
AS lp LEFT JOIN citizen AS ci ON lp.NIK = ci.NIK LEFT JOIN
citizen_status AS cs ON ci.status_id = cs.status_id WHERE lp.nop
= '".$result['nop']."'!";
$Query_owner = pg_Query($sql);
$data_owner = null;
if(pg_num_rows($Query_owner)>0){
$data_owner = array();
while ($result_sub = pg_fetch_assoc($Query_owner)) {
$data_owner[] = $result_sub;
}
$data['owner'] = $data_owner;
}
$data['object'] = $data_object;
return $data;
}
else{
return 0;
}
```

```
//Kode Program Pencarian Kapling Tanah Berdasarkan No Objek Pajak Berupa
```

```
// Peta
```

```
// method mendapatkan layer dari object tanah berdasarkan nomor
// object tanah
public function object_layer($object_id){
    $sql = "SELECT ST_AsGeoJSON(la.geom) As geometry, la.nop,
ST_Y(ST_CENTROID(la.geom)) AS lat, ST_X(ST_CENTROID(la.geom)) AS
lng FROM land As la WHERE la.nop = '$object_id'";
    $geojson = array(
        'type' => 'FeatureCollection',
        'features' => array()
    );
    $Query = pg_Query($sql);
    if(pg_num_rows($Query)==0) return 0;
    while($edge=pg_fetch_assoc($Query)){
        $feature = array(
            'type' => 'Feature',
            'geometry' => json_decode($edge['geometry'], true),
            'properties' => array(
                'object' => $edge['nop'],
                'center' => array(
                    'lat' => $edge['lat'],
                    'lng' => $edge['lng']
                )));
        array_push($geojson['features'], $feature);
    }
    return $geojson;
}
```

c. Contoh Luaran Program

The screenshot shows a search interface for land numbers. A search bar at the top contains the number '13.06.060.039.003.0117.0'. Below the search bar, there are two tabs: 'Information' and 'Location'. The 'Information' tab is selected, displaying details about the land. Key information includes:

- Status: High Ancestral Property
- Address: Padang Lua I
- Size: 130 m²
- Land Owner: 1301034607780004 - Wisnar Dinar - (60 years old) (Asli)
- Land History: 1301034607780004 - Wisnar Dinar - (60 years old) (Asli) - (2017-05-17)
1306060103890006 - Amrudin - (75 years old) (Peraatau) - (2016-07-17)
1306060103890006 - Ismail - (28 years old) (Asli) - (2015-06-13)
1306060103920001 - Ahmad Rovi - (25 years old) (Asli) - (2014-07-06)
1306060106700001 - Abrar - (47 years old) (Asli) - (2013-07-06)
1301032104680004 - Syahrial - (48 years old) (Asli) - (2012-06-07)
- House: 1 House
- A091: Status: Family Property
Owner Building: Wisnar Dinar Abrar
Family Card Number: 138809809090901
3 People

Gambar 1. Hasil Data Normal Mencari Kapling tanah Berupa Informasi Teks

This is a detailed view of a house record. The address is Padang Lua I. The owner is listed as Wisnar Dinar (60 years old, Man). The resident section lists three individuals:


Resident	Family Card Number	Gender	Age	Clan
Aurelina Afrilia	1301034504110001	Woman	6 years old	Piliang Clan
Kambali Mandala	1300001911750008	Woman	33 years old	Piliang Clan
Wisnar Dinar	1301034607780004	Man	60 years old	Piliang Clan

Gambar 2. House Information

This is a detailed view of a family record. The house number is A091 and there are 3 people in the family. The family members listed are:

Resident	House Number	Gender	Age	Clan
Aurelina Afrilia	A091	Woman	6 years old	Piliang Clan
Kambali Mandala	3 People	Woman	33 years old	Piliang Clan
Wisnar Dinar	1301034607780004	Man	60 years old	Piliang Clan

Gambar 3. Family Information



Gambar 4. Hasil Pencarian Kapling Tanah Berupa Peta

2. Menampilkan List Tanah

a. Use Case Scenario

Tabel 3. Skenario Menampilkan List Tanah Berupa Informasi Teks

<i>Use Case Name</i>	Menampilkan <i>Land List</i> Berupa Informasi Teks
<i>Participating Actor</i>	<i>User</i>
<i>Flow Of Events</i>	<ol style="list-style-type: none"> 1. User memilih menu <i>land</i> 2. Sistem akan menampilkan submenu 3. User memilih menu <i>land list</i> 4. Sistem akan menampilkan menu <i>land list</i> 5. User memilih keriteria yang telah disediakan dan mengklik button <i>show</i> 6. Sistem menampilkan data berdasarkan kriteria yang telah dipilih
<i>Entry condition</i>	<i>User</i> telah login
<i>Exit Condition</i>	Sistem Menampilkan data berdasarkan kriteria yang dipilih

Tabel 4. Prosedur Menampilkan List Tanah Berupa Peta

<i>Use Case Name</i>	Menampilkan Land List Berupa Peta
<i>Participating Actor</i>	<i>User</i>

<i>Flow Of Events</i>	1. <i>User</i> memilih menu <i>land</i>
	2. Sistem akan menampilkan submenu
	3. <i>User</i> memilih menu <i>land list</i>
	4. Sistem akan menampilkan menu <i>land list</i>
	5. <i>User</i> memilih tab <i>map</i>
	6. Sistem menampilkan halaman tab <i>map</i>
	7. <i>User</i> memilih keriteria yang telah disediakan dan mengklik button <i>show</i>
	8. Sistem menampilkan peta berdasarkan kriteria yang telah dipilih
<i>Entry condition</i>	<i>User</i> telah login
<i>Exit Condition</i>	Sistem Menampilkan data berdasarkan kriteria yang dipilih

b. Kode Program

```
// Menampilkan List Tanah Berupa Informasi Teks
//method untuk mendapatkan daftar object tanah;
public function object_list($clan,$status,$owned,$pawned)
{
$condition_owner = array();
$condition = array();
$where_owner = "";
$where = "";
$where_end = "";
if($clan!="all"){
$cond = " MD5(ci.clan_id::teks)= '$clan'";
array_push($condition_owner, $cond);
$where_end = ' WHERE owner IS NOT NULL';
}
if($status!="all"){
$cond = 'la.high_property = '.$status;
array_push($condition, $cond);
}
if($owned!="all"){
$cond = 'ci.status_id = '.$owned;
array_push($condition_owner, $cond);
$where_end = ' WHERE owner IS NOT NULL';
}
if($pawned!="all"){
$cond = 'la.pawning = '.$pawned;
array_push($condition, $cond);
}
array_push($condition_owner, "lp.nop = la.nop");
array_push($condition, "true");
$where_owner = "WHERE " . implode(" AND ", $condition_owner);
$where = "WHERE " . implode(" AND ", $condition);
```

```

$sql = "SELECT * FROM (SELECT la.nop, la.land_size,
ci.building_size,(SELECT array_to_json(array_agg(f)) FROM (SELECT
ci.nik, ci.name AS name, cs.name AS status, EXTRACT(YEAR FROM
AGE(ci.born_date)) AS age FROM land_proprietary AS lp LEFT JOIN
pemilik AS ci ON lp.nik = ci.nik LEFT JOIN citizen_status AS cs ON
ci.status_id = cs.status_id WHERE owner) AS f) AS owner FROM land
AS la left join land_proprietary AS lp on la.nop=lp.nop LEFT JOIN
pemilik AS ci ON lp.nik = ci.nik WHERE) as fs WHERE_end";
$Query = pg_Query($sql);
if(pg_num_rows($Query) > 0){
while ($data = pg_fetch_assoc($Query)){
$data['nop'] = $data['nop'];
$data['land_size'] = $data['land_size'];
$data['building_size'] = $data['building_size'];
$data['owner'] = json_decode($data['owner']);
$data_a[] = $data;
}
return $data_a;
}
else{
return 0;
}

// Menampilkan List Tanah Berupa Peta
//file proses.php
else if($do == 'g_map_land_clan'){
header('Content-Type: application/json');
$current_selected_clan= $_GET['current_selected_clan'];
$current_selected_status= $_GET['current_selected_status'];
$current_selected_owner=$_GET['current_selected_owner'];
$current_selected_pawned =$_GET['current_selected_pawned'];
if($current_selected_clan == 'all' && $current_selected_status ==
'all' && $current_selected_owner == 'all' &&
$current_selected_pawned == 'all'){
$m = new land();
$data = $m->load_land_map();
echo json_encode($data);
}
else if($current_selected_clan == 'all' && $current_selected_status
!= 'all' && $current_selected_owner == 'all' &&
$current_selected_pawned != 'all'){
$m = new land();
$data = $m->load_land_map1
($current_selected_status,$current_selected_pawned);
echo json_encode($data);
}

else if($current_selected_clan == 'all' && $current_selected_status
!= 'all' && $current_selected_owner == 'all' &&
$current_selected_pawned == 'all'){
$m = new land();
$data = $m->load_land_map2($current_selected_status );
echo json_encode($data);
}
}

```

```

else if($current_selected_clan == 'all' && $current_selected_status
== 'all' && $current_selected_owner != 'all' &&
$current_selected_pawned == 'all'){
$m = new land();
$data = $m->load_land_map3($current_selected_owner );
echo json_encode($data);
}
else if($current_selected_clan == 'all' && $current_selected_status
== 'all' && $current_selected_owner == 'all' &&
$current_selected_pawned != 'all'){
$m = new land();
$data = $m->load_land_map4($current_selected_pawned);
echo json_encode($data);
}
else if($current_selected_clan == 'all' && $current_selected_status
== 'all' && $current_selected_owner != 'all' &&
$current_selected_pawned != 'all'){
$m = new land();
$data = $m-
>load_land_map5($current_selected_owner,$current_selected_pawned);e
cho json_encode($data);
}
else if(strlen($current_selected_clan) == 32 &&
$current_selected_status == 'all' && $current_selected_owner ==
'all' && $current_selected_pawned == 'all'){
$m = new land();
$data = $m->load_land_map6($current_selected_clan);
echo json_encode($data);
}
else if(strlen($current_selected_clan) == 32 &&
$current_selected_status != 'all' && $current_selected_owner ==
'all' && $current_selected_pawned == 'all'){
$m = new land();
$data = $m-
>load_land_map7($current_selected_clan,$current_selected_status);
echo json_encode($data);
}
else if(strlen($current_selected_clan) == 32 &&
$current_selected_status != 'all' && $current_selected_owner !=
'all' && $current_selected_pawned == 'all'){
$m = new land();
$data = $m-
>load_land_map12($current_selected_clan,$current_selected_status,$c
urrent_selected_owner);
echo json_encode($data);
}
else if(strlen($current_selected_clan) == 32 &&
$current_selected_status == 'all' && $current_selected_owner !=
'all' && $current_selected_pawned == 'all'){
$m = new land();
$data = $m-
>load_land_map8($current_selected_clan,$current_selected_owner);
echo json_encode($data);
}

```

```

else if(strlen($current_selected_clan) == 32 &&
$current_selected_status == 'all' && $current_selected_owner ==
'all' && $current_selected_pawned != 'all'){
$m = new land();
$data = $m-
>load_land_map9($current_selected_clan,$current_selected_pawned);
echo json_encode($data);
}
else if(strlen($current_selected_clan) == 32 &&
$current_selected_status == 'all' && $current_selected_owner !=
'all' && $current_selected_pawned != 'all'){
$m = new land();
$data = $m-
>load_land_map10($current_selected_clan,$current_selected_owner,cur
rent_selected_pawned);
echo json_encode($data);
}
else if(strlen($current_selected_clan) == 32 &&
$current_selected_status != 'all' && $current_selected_owner !=
'all' && $current_selected_pawned != 'all'){
$m = new land();
$data = $m-
>load_land_map11($current_selected_clan,$current_selected_status,$c
urrent_selected_owner,$current_selected_pawned );
echo json_encode($data);
}
else{
echo 0;
}

-----  

// file Class.php ( method mendapatkan layer dari list tanah)
public function load_land_map(){
$sql="SELECT ST_AsGeoJSON(la.geom) As geometry,
ST_Y(ST_CENTROID(la.geom)) AS lat, ST_X(ST_CENTROID(la.geom)) AS
lng, la.nop, case when MD5(ci.clan_id):teks)='all' then 1 else 0
end as a FROM land as la LEFT JOIN land_proprietary As lp on
la.nop= lp.nop LEFT JOIN citizen AS ci ON lp.nik = ci.nik LEFT JOIN
citizen_status AS cs ON ci.status_id = cs.status_id";
$Query = pg_Query($sql);
if(pg_num_rows($Query) > 0){
while ($data = pg_fetch_assoc($Query)){
$data_a[] = $data;
}
return $data_a;
}

public function
load_land_map1($current_selected_status,$current_selected_pawned){$
sql="SELECT ST_AsGeoJSON(la.geom) As geometry,
ST_Y(ST_CENTROID(la.geom)) AS lat, ST_X(ST_CENTROID(la.geom)) AS
lng, la.nop, case when la.high_property='$current_selected_status'
AND la.pawning='$current_selected_pawned' then 1 else 0 end as a
FROM land as la LEFT JOIN land_proprietary As lp on la.nop= lp.nop
LEFT JOIN citizen AS ci ON lp.nik = ci.nik LEFT JOIN citizen_status
AS cs ON ci.status_id = cs.status_id";

```

```

$Query = pg_Query($sql);
if(pg_num_rows($Query) > 0){
while ($data = pg_fetch_assoc($Query)){
$data_a[] = $data;
}
return $data_a;
}
public function load_land_map2 ($current_selected_status){
$sql="SELECT ST_AsGeoJSON(la.geom) As geometry,
ST_Y(ST_CENTROID(la.geom)) AS lat, ST_X(ST_CENTROID(la.geom)) AS
lng, la.nop, case when la.high_property='$current_selected_status'
then 1 else 0 end as a FROM land as la LEFT JOIN land_proprietary
As lp on la.nop= lp.nop LEFT JOIN citizen AS ci ON lp.nik = ci.nik
LEFT JOIN citizen_status AS cs ON ci.status_id = cs.status_id";
$Query = pg_Query($sql);
if(pg_num_rows($Query) > 0){
while ($data = pg_fetch_assoc($Query)){
$data_a[] = $data;
}
return $data_a;
}
public function load_land_map4 ($current_selected_pawned){
$sql="SELECT ST_AsGeoJSON(la.geom) As geometry,
ST_Y(ST_CENTROID(la.geom)) AS lat, ST_X(ST_CENTROID(la.geom)) AS
lng, la.nop, case when la.pawning='$current_selected_pawned' then
1 else 0 end as a FROM land as la LEFT JOIN land_proprietary As lp
on la.nop= lp.nop LEFT JOIN citizen AS ci ON lp.nik = ci.nik LEFT
JOIN citizen_status AS cs ON ci.status_id = cs.status_id";
$Query = pg_Query($sql);
if(pg_num_rows($Query) > 0){
while ($data = pg_fetch_assoc($Query)){
$data_a[] = $data;
}
return $data_a;
}
public function load_land_map5
($current_selected_owner,$current_selected_pawned){
$sql="SELECT ST_AsGeoJSON(la.geom) As geometry,
ST_Y(ST_CENTROID(la.geom)) AS lat, ST_X(ST_CENTROID(la.geom)) AS
lng, la.nop, case when ci.status_id='$current_selected_owner' AND
la.pawning='$current_selected_pawned' then 1 else 0 end as a FROM
land as la LEFT JOIN land_proprietary As lp on la.nop= lp.nop LEFT
JOIN citizen AS ci ON lp.nik = ci.nik LEFT JOIN citizen_status AS
cs ON ci.status_id = cs.status_id";
$Query = pg_Query($sql);
if(pg_num_rows($Query) > 0){
while ($data = pg_fetch_assoc($Query)){
$data_a[] = $data;
}
return $data_a;
}
public function load_land_map6 ($current_selected_clan){
$sql="SELECT ST_AsGeoJSON(la.geom) As geometry,
ST_Y(ST_CENTROID(la.geom)) AS lat, ST_X(ST_CENTROID(la.geom)) AS

```

```

lng, la.nop, case when
MD5(ci.clan_id::teks)='$current_selected_clan' then 1 else 0 end as
a FROM land as la LEFT JOIN land_proprietary As lp on la.nop=
lp.nop LEFT JOIN citizen AS ci ON lp.nik = ci.nik LEFT JOIN
citizen_status AS cs ON ci.status_id = cs.status_id";
$Query = pg_Query($sql);
if(pg_num_rows($Query) > 0){
while ($data = pg_fetch_assoc($Query)){
$data_a[] = $data;
}
return $data_a;
}
public function load_land_map7 ($current_selected_clan
,$current_selected_status){
$sql="SELECT ST_AsGeoJSON(la.geom) As geometry,
ST_Y(ST_CENTROID(la.geom)) AS lat, ST_X(ST_CENTROID(la.geom)) AS
lng, la.nop, case when
MD5(ci.clan_id::teks)='$current_selected_clan' AND
la.high_property='$current_selected_status' then 1 else 0 end as a
FROM land as la LEFT JOIN land_proprietary As lp on la.nop= lp.nop
LEFT JOIN citizen AS ci ON lp.nik = ci.nik LEFT JOIN citizen_status
AS cs ON ci.status_id = cs.status_id";
$Query = pg_Query($sql);
if(pg_num_rows($Query) > 0){
while ($data = pg_fetch_assoc($Query)){
$data_a[] = $data;
}
return $data_a;
}
public function load_land_map8
($current_selected_clan,$current_selected_owner){
$sql="SELECT ST_AsGeoJSON(la.geom) As geometry,
ST_Y(ST_CENTROID(la.geom)) AS lat, ST_X(ST_CENTROID(la.geom)) AS
lng, la.nop, case when
MD5(ci.clan_id::teks)='$current_selected_clan' AND
ci.status_id='\$current_selected_owner' then 1 else 0 end as a FROM
land as la LEFT JOIN land_proprietary As lp on la.nop= lp.nop LEFT
JOIN citizen AS ci ON lp.nik = ci.nik LEFT JOIN citizen_status AS
cs ON ci.status_id = cs.status_id";
$Query = pg_Query($sql);
if(pg_num_rows($Query) > 0){
while ($data = pg_fetch_assoc($Query)){
$data_a[] = $data;
}
return $data_a;
}
public function load_land_map9
($current_selected_clan,$current_selected_pawned){
$sql="SELECT ST_AsGeoJSON(la.geom) As geometry,
ST_Y(ST_CENTROID(la.geom)) AS lat, ST_X(ST_CENTROID(la.geom)) AS
lng, la.nop, case when
MD5(ci.clan_id::teks)='\$current_selected_clan' AND
la.pawning='\$current_selected_pawned' then 1 else 0 end as a FROM
land as la LEFT JOIN land_proprietary As lp on la.nop= lp.nop LEFT

```

```

JOIN citizen AS ci ON lp.nik = ci.nik LEFT JOIN citizen_status AS
cs ON ci.status_id = cs.status_id";
$Query = pg_Query($sql);
if(pg_num_rows($Query) > 0){
while ($data = pg_fetch_assoc($Query)){
$data_a[] = $data;
}
return $data_a;
}
public function load_land_map10
($current_selected_clan,$current_selected_owner,$current_selected_p
awned){
$sql="SELECT ST_AsGeoJSON(la.geom) As geometry,
ST_Y(ST_CENTROID(la.geom)) AS lat, ST_X(ST_CENTROID(la.geom)) AS
lng, la.nop, case when
MD5(ci.clan_id::teks)='\$current_selected_clan' AND
ci.status_id='\$current_selected_owner' AND
la.pawning='\$current_selected_pawned' then 1 else 0 end as a FROM
land as la LEFT JOIN land_proprietary As lp on la.nop= lp.nop LEFT
JOIN citizen AS ci ON lp.nik = ci.nik LEFT JOIN citizen_status AS
cs ON ci.status_id = cs.status_id";
$Query = pg_Query($sql);
if(pg_num_rows($Query) > 0){
while ($data = pg_fetch_assoc($Query)){
$data_a[] = $data;
}
return $data_a;
}
public function load_land_map11
($current_selected_clan,$current_selected_status,$current_selected_
owner,$current_selected_pawned){
$sql="SELECT ST_AsGeoJSON(la.geom) As geometry,
ST_Y(ST_CENTROID(la.geom)) AS lat, ST_X(ST_CENTROID(la.geom)) AS
lng, la.nop, case when
MD5(ci.clan_id::teks)='\$current_selected_clan' AND
la.high_property='\$current_selected_status' AND
ci.status_id='\$current_selected_owner' AND
la.pawning='\$current_selected_pawned' then 1 else 0 end as a FROM
land as la LEFT JOIN land_proprietary As lp on la.nop= lp.nop LEFT
JOIN citizen AS ci ON lp.nik = ci.nik LEFT JOIN citizen_status AS
cs ON ci.status_id = cs.status_id";
$Query = pg_Query($sql);
if(pg_num_rows($Query) > 0){
while ($data = pg_fetch_assoc($Query)){
$data_a[] = $data;
}
return $data_a;
}
public function load_land_map12
($current_selected_clan,$current_selected_status,$current_selected_
owner){
$sql="SELECT ST_AsGeoJSON(la.geom) As geometry,
ST_Y(ST_CENTROID(la.geom)) AS lat, ST_X(ST_CENTROID(la.geom)) AS
lng, la.nop, case when
MD5(ci.clan_id::teks)='\$current_selected_clan' AND
la.high_property='\$current_selected_status' AND

```

```


ci.status_id='$current_selected_owner' then 1 else 0 end as a FROM
land as la LEFT JOIN land_proprietary As lp on la.nop= lp.nop LEFT
JOIN citizen AS ci ON lp.nik = ci.nik LEFT JOIN citizen_status AS
cs ON ci.status_id = cs.status_id";
$Query = pg_Query($sql);
if(pg_num_rows($Query) > 0){
while ($data = pg_fetch_assoc($Query)) {
    $data_a[] = $data;
}
return $data_a;
}
public function load_land_map3 ($current_selected_owner){
    $sql="SELECT ST_AsGeoJSON(la.geom) As geometry,
ST_Y(ST_CENTROID(la.geom)) AS lat, ST_X(ST_CENTROID(la.geom)) AS
lng, la.nop, case when ci.status_id='$current_selected_owner' then
1 else 0 end as a FROM land as la LEFT JOIN land_proprietary As lp
on la.nop= lp.nop LEFT JOIN citizen AS ci ON lp.nik = ci.nik LEFT
JOIN citizen_status AS cs ON ci.status_id = cs.status_id";
$Query = pg_Query($sql);
if(pg_num_rows($Query) > 0){
while ($data = pg_fetch_assoc($Query)) {
    $data_a[] = $data;
}
return $data_a;
}

```

c. Contoh luaran program

Land	Land Size	Building Size	Owner
13.06.090.039.001.0146.0 410 m ²	212 m ²	-	• 1399026883651201 - Novi Eka Nasyidah
13.06.090.039.001.0147.0 112 m ²	132 m ²	-	• 1399024824493007 - Ukip Prasetyo
13.06.090.039.001.0154.0 36 m ²	36 m ²	-	• 1399026712502002 - Rani
13.06.090.039.001.0155.0 159 m ²	96 m ²	-	• 1399026710380003 - Joni Indra
13.06.090.039.001.0156.0 120 m ²	90 m ²	-	• 1399026552080003 - Jemaludin
13.06.090.039.001.0170.0 179 m ²	0 m ²	-	• 13990262012501707 - Purwanto Lazuardi
13.06.090.039.001.0178.0 85 m ²	48 m ²	-	• 1399026205842001 - Mala Budi Andi
13.06.090.039.001.0184.0 30 m ²	44 m ²	-	• 1399026207740001 - Yulia Syahrial
13.06.090.039.001.0188.0 88 m ²	160 m ²	-	• 1399001713490504 - Rusman Uda Anggriawan S.Pt
13.06.090.039.001.0194.0 300 m ²	120 m ²	-	• 1306066606470001 - Annel

Gambar 5. Hasil Menampilkan List Tanah Berupa Informasi Teks



Gambar 6. Hasil Menampilkan List Tanah Berupa Peta

3. Mengelola Data Land History

a. Use Case Skenario

Tabel 5. Skenario Menampilkan Data Land history

<i>Use Case Name</i>	Menampilkan data History Land
<i>Participating Actor</i>	<i>User</i>
<i>Flow Of Events</i>	<ol style="list-style-type: none"> 1. <i>User</i> memilih menu <i>land</i> 2. Sistem akan menampilkan sub menu 3. <i>User</i> memilih menu <i>land history</i> 4. Sistem akan menampilkan data <i>history land</i>
<i>Entry condition</i>	<i>User</i> telah login
<i>Exit Condition</i>	<i>User</i> dapat melihat informasi <i>history land</i>

Tabel 6. Skenario Menginputkan Data Land history

<i>Use Case Name</i>	Menambah Data History Land
<i>Participating Actor</i>	<i>User</i>
<i>Flow Of Events</i>	<ol style="list-style-type: none"> 1. <i>User</i> memilih menu <i>land</i> 2. Sistem akan menampilkan sub menu 3. <i>User</i> memilih menu <i>land history</i>

	4. Sistem akan menampilkan menu <i>land history</i> 5. User mengklik button <i>displacement of land owner</i> 6. Sistem akan form menambah data <i>history land</i> 7. User mengisi form dan memilih button <i>save</i> 8. Sistem akan menyimpan perubahan dalam <i>database</i>
<i>Entry condition</i>	User telah login
<i>Exit Condition</i>	Sistem menyimpan perubahan data ke <i>database</i> dan membuka kembali halaman <i>land history</i>

b. Kode Program

```
//Kode Program Menampilkan Data History Land
//method untuk query menampilkan data history land
public function load_history(){
    $sql="select b.nop, b.state, b.tgl, c.name, b.coment FROM
    land_proprietary as b LEFT JOIN pemilik as c ON b.nik=c.nik ORDER
    BY nop, tgl desc ";
    $query = pg_query($sql);
    if(pg_num_rows($query) > 0){
        while ($data = pg_fetch_assoc($query)){
            $data_a[] = $data;
        }
    }
    return $data_a;
}
// Menginputkan Data History Land
//method untuk query menginputkan data history land
public function insert($data){
    $sqlICN="INSERT INTO land_proprietary(nop, nik, state, tgl, coment)
    VALUES ";
    $sqlICN.=(".".()."$.data['nop']."' , '$.data['nik]' , '$.data['state
    ']' , '$.data['tgl]' , '$.data['coment']' ");
    $sql=$sqlICN.';';
    $query = pg_query($sql);
    if($query){
        return 1;
    }
    else{
        return 0;
    }
}
```

c. Contoh Luaran Program

Land History (All Land History)						
+ Displacement Of Landowners						
Search: 13.06.060.039.003.0117						
Show 10 entries						
No	NOP	Date	Name	State	Comment	
484	13.06.060.039.003.0117.0	2017-05-17	Wisnar Dinar	Warisan		
485	13.06.060.039.003.0117.0	2016-07-17	Hikmah Purnama	Warisan		
486	13.06.060.039.003.0117.0	2015-06-13	Puti Kulindam Suci	Warisan		
487	13.06.060.039.003.0117.0	2014-07-08	Ahmad Roni	Warisan		
488	13.06.060.039.003.0117.0	2013-07-08	Ridho Sofaris	Warisan		
489	13.06.060.039.003.0117.0	2012-06-07	Rita Masri	Warisan		

Showing 1 to 6 of 6 entries (filtered from 1,284 total entries)

Previous [1](#) Next

Gambar 4. Hasil Menampilkan Data Land history

Gambar 5. Hasil Menginputkan Data Land history

4. Pencarian Data Bangunan Berdasarkan Nomor Bangunan

a. Use Case Skenario

Tabel 7. Skenario Pencarian Data Bangunan Berdasarkan Nomor Bangunan Berupa
Informasi teks

<i>Use case name</i>	Pencarian Data Bangunan Berdasarkan Nomor Bangunan Berupa Informasi teks
<i>Participating Actor</i>	<i>User</i>
<i>Flow Of Events</i>	1. <i>User</i> memilih menu <i>building</i> 2. Sistem akan menampilkan sub menu 3. <i>User</i> memilih menu <i>building search</i>

	4. Sistem akan menampilkan menu <i>building search</i> 5. User memasukan nomor bangunan 6. Sistem akan menampilkan informasi teks mengenai kapling bangunan
<i>Entry condition</i>	User telah login
<i>Exit Condition</i>	User dapat melihat informasi teks mengenai kapling tanah yang diinginkan
<i>Alternative Course</i>	a. User memilih menu <i>building</i> b. Sistem akan menampilkan sub menu c. User memilih menu <i>building search</i> d. Sistem akan menampilkan menu <i>building search</i> 7. User memasukan nomor bangunan 8. Sistem akan menampilkan "Data Not Found"

Tabel 8. Skenario Pencarian Data Bangunan Berdasarkan Nomor Bangunan Berupa

Peta

<i>Use case name</i>	Pencarian Data Bangunan Berdasarkan Nomor Bangunan Berupa Peta
<i>Participating Actor</i>	User
<i>Flow Of Events</i>	1. User memilih menu <i>building</i> 2. Sistem akan menampilkan sub menu 3. User memilih menu <i>building search</i> 4. Sistem akan menampilkan menu <i>building search</i> 5. User memasukan nomor bangunan 6. Sistem akan menampilkan informasi teks mengenai kapling bangunan 7. User memilih tab <i>map</i>

	8. Sistem akan menampilkan lokasi berdasarkan nomor bangunan yang diinputkan
<i>Entry condition</i>	User telah login
<i>Exit Condition</i>	User dapat melihat lokasi bangunan berdasarkan nomor bangunan

b. Kode Program


```
// Pencarian Data Bangunan Berdasarkan Nomor Bangunan Berupa Informasi
// Teks
// Method untuk memanggil data dari database menggunakan bahasa
// pemrograman php
public function find_house($id){
  // query berdasarkan pencarian bangunan
  $sql = "SELECT ho.no_house, ho.status, ho.condition, la.nop AS
nop, la.high_property AS land_status, jo.name AS address FROM
building AS ho, land AS la, jorong AS jo WHERE
ST_CONTAINS(la.geom, ST_CENTROID(ho.geom)) AND
ST_CONTAINS(jo.geom, ST_CENTROID(ho.geom)) AND
ST_CONTAINS(jo.geom, ST_CENTROID(ho.geom)) AND ho.no_house =
'$id'";
  $Query = pg_Query($sql);
  if(pg_num_rows($Query) > 0){
    //generate informasi bangunan;
    $result = pg_fetch_assoc($Query);
    $data['no_house'] = $result['no_house'];
    $data['status'] = $result['status'];
    $data['condition'] = $result['condition'];
    $data['land']['nop'] = $result['nop'];
    $data['land']['status'] = $result['land_status'];
    $data['address'] = $result['address'];
    //mencari pemilik rumah
    $sql = "SELECT ci.nik, ci.name, ci.gender, EXTRACT(YEAR FROM
AGE(ci.born_date)) AS age, ci.status FROM building as b LEFT JOIN
building_family AS how ON b.id=how.id_building LEFT JOIN citizen
AS ci ON how.family_no = ci.family_no WHERE b.no_house =
'".$result['no_house']."' ";
    $Query_owner = pg_Query($sql);
    $data_owner = null;
    if(pg_num_rows($Query_owner)>0){
      $data_owner = array();
      while ($result_sub = pg_fetch_assoc($Query_owner)) {
        $data_owner[] = $result_sub;
      }
    }
    $data['owner'] = $data_owner;
  }
}
```

```

//mencari penghuni rumah
$sql = "SELECT ci.family_no, COUNT(ci.nik) AS resident
FROM citizen AS ci
LEFT JOIN building_family as b ON ci.family_no=b.family_no
LEFT JOIN building as c ON b.id_building=c.id
WHERE no_house = '".$result['no_house']."' GROUP BY
ci.family_no";
$Query_fcn = pg_Query($sql);
$data_fcn = null;
if(pg_num_rows($Query_fcn)>0){
$data_fcn = array();
while ($result_sub_fcn = pg_fetch_assoc($Query_fcn)) {
$data_fcn[] = $result_sub_fcn;
}
}
$data['resident'] = $data_fcn;
return $data;
} else{
return 0;
}
// Pencarian Data Bangunan Berdasarkan Nomor Bangunan Berupa Peta
//method mendapatkan layer dari object bangunan berdasarkan nomor
bangunan
public function house_layer($no_house){
$sql = "SELECT ST_AsGeoJSON(ho.geom) As geometry, ho.no_house,
ST_Y(ST_CENTROID(ho.geom)) AS lat, ST_X(ST_CENTROID(ho.geom)) AS
lng FROM building As ho WHERE ho.no_house = '$no_house'";
$geojson = array(
'type' => 'FeatureCollection',
'features' => array()
);
$Query = pg_Query($sql);
if(pg_num_rows($Query)==0)
return 0;
while($edge=pg_fetch_assoc($Query)){
$feature = array(
'type' => 'Feature',
'geometry' => json_decode($edge['geometry'], true),
'properties' => array(
'object' => $edge['no_house'],
'center' => array(
'lat' => $edge['lat'],
{lng' => $edge['lng']
));
array_push($geojson['features'], $feature);
}
return $geojson;
}

```

c. Contoh Luaran Program




Gambar 9. Hasil Data Normal Mencari Bangunan Berdasarkan Nomor Bangunan



Gambar 10. Land Information



Gambar 11. Family Information



Gambar 12. Hasil Mencari Lokasi Bangunan Berdasarkan Nomor Bangunan

5. Menampilkan List Bangunan

a. Use Case Skenario

Tabel 9. Skenario Menampilkan List Bangunan Berupa Informasi Teks

Use Case Name	Menampilkan Building List Berupa Informasi Teks
Participating Actor	User
Flow Of Events	<ol style="list-style-type: none"> 1. User memilih menu building 2. Sistem akan menampilkan submenu 3. User memilih menu building list 4. Sistem akan menampilkan menu building list
	<ol style="list-style-type: none"> 5. User memilih keriteria yang telah disediakan dan mengklik button show 6. Sistem menampilkan data berdasarkan kriteria yang telah dipilih
Entry condition	User telah login
Exit Condition	Sistem Menampilkan data berdasarkan kriteria yang dipilih

Tabel 10. Skenario Menampilkan List Bangunan Berupa Peta

Use Case Name	Menampilkan building List Berupa Peta
Participating Actor	User
Flow Of Events	<ol style="list-style-type: none"> 1. User memilih menu building 2. Sistem akan menampilkan submenu 3. User memilih menu building list 4. Sistem akan menampilkan menu building list

	<p>5. User memilih tab map</p> <p>6. Sistem menampilkan halaman tab map</p> <p>7. User memilih keriteria yang telah disediakan dan mengklik button show</p> <p>8. Sistem menampilkan peta berdasarkan kriteria yang telah dipilih</p>
Entry condition	User telah login
Exit Condition	Sistem Menampilkan data berdasarkan kriteria yang dipilih

b. Kode Program

```
//Menampilkan List Bangunan Berupa Informasi Teks
// file class.php
else if($do == 'g_building_all'){
header('Content-Type: application/json');
$current_selected_clan=$_GET['current_selected_clan'];
$current_selected_owner=$_GET['current_selected_owner'];
$current_selected_owner_land=$_GET['current_selected_owner_land'];
$current_selected_status=$_GET['current_selected_status'];
if($current_selected_clan == 'all' && $current_selected_owner == 'all' && $current_selected_owner_land == 'all' && $current_selected_status == 'all'){
$m = new building();
$data = $m->load();
echo json_encode($data);
}
else if($current_selected_clan == 'all' && $current_selected_owner != 'all' && $current_selected_owner_land != 'all' && $current_selected_status != 'all'){
$m = new building();
$data = $m->load_building_all1($current_selected_owner,
$current_selected_owner_land,$current_selected_status );
echo json_encode($data);
}
else if($current_selected_clan == 'all' && $current_selected_owner == 'all' && $current_selected_owner_land != 'all' && $current_selected_status != 'all'){
$m = new building();
$data = $m-
>load_building_all15($current_selected_owner_land,$current_selected_
status );
echo json_encode($data);
}
else if($current_selected_clan == 'all' && $current_selected_owner == 'all' && $current_selected_owner_land == 'all' && $current_selected_status != 'all'){
$m = new building();
$data = $m->load_building_all16($current_selected_status );
echo json_encode($data);
}
```

```

}
else if($current_selected_clan == 'all' && $current_selected_owner
!= 'all' && $current_selected_owner_land == 'all' &&
$current_selected_status != 'all'){
$m = new building();
$data = $m->load_building_all7($current_selected_owner,
$current_selected_status );
echo json_encode($data);
}
else if($current_selected_clan == 'all' && $current_selected_owner
!= 'all' && $current_selected_owner_land == 'all' &&
$current_selected_status == 'all'){
$m = new building();
$data = $m->load_building_all8($current_selected_owner);
echo json_encode($data);
}
else if(strlen($current_selected_clan) == 32 &&
$current_selected_owner == 'all' && $current_selected_owner_land !=
'all' && $current_selected_status != 'all'){
$m = new building();
$data = $m->load_building_all2($current_selected_clan,
$current_selected_owner_land,$current_selected_status );
echo json_encode($data);
}
else if(strlen($current_selected_clan) == 32 &&
$current_selected_owner != 'all' && $current_selected_owner_land ==
'all' && $current_selected_status != 'all'){
$m = new building();
$data = $m-
>load_building_all3($current_selected_clan,$current_selected_owner,
$current_selected_status );
echo json_encode($data);
}
else if(strlen($current_selected_clan) == 32 &&
$current_selected_owner != 'all' && $current_selected_owner_land !=
'all' && $current_selected_status == 'all'){
$m = new building();
$data = $m-
>load_building_all4($current_selected_clan,$current_selected_owner,
$current_selected_owner_land);
echo json_encode($data);
}
else if(strlen($current_selected_clan) == 32 &&
$current_selected_owner != 'all' && $current_selected_owner_land !=
'all' && $current_selected_status != 'all'){
$m = new building();
$data = $m-
>load_building_all($current_selected_clan,$current_selected_owner,
$current_selected_owner_land,$current_selected_status );
echo json_encode($data);
}
else{
echo 0;
}
-----
```

```

// file Class.php
public function
load_building_all1($current_selected_owner,$current_selected_owner_
land, $current_selected_status){
$Sql="SELECT b.* ,c.family_no,c.name FROM building b LEFT JOIN
building_family f ON b.id=f.id_building LEFT JOIN citizen c ON
c.nik=b.nik LEFT JOIN clans as k on c.clan_id=k.clan_id LEFT JOIN
citizen_status as j on c.status_id=j.status_id LEFT JOIN
land_proprietary as m on m.nik=c.nik LEFT JOIN land as l ON
l.nop=m.nop LEFT JOIN owner_state as d ON d.id_state=l.id_state
where c.status_id='$current_selected_owner' AND
l.id_state='$current_selected_owner_land' AND
l.high_property='$current_selected_status'";
$Query = pg_Query($Sql);
if(pg_num_rows($Query) > 0){
$i=array();
while ($data = pg_fetch_assoc($Query)){
$data_a[$data['id']][] = $data;
}
return $data_a;
}
public function load_building_all5($current_selected_owner_land,
$current_selected_status){
$Sql="SELECT b.* ,f.family_no,c.name FROM building b LEFT JOIN
building_family f ON b.id=f.id_building LEFT JOIN citizen c ON
c.nik=b.nik LEFT JOIN clans as k on c.clan_id=k.clan_id LEFT JOIN
citizen_status as j on c.status_id=j.status_id LEFT JOIN
land_proprietary as m on m.nik=c.nik LEFT JOIN land as l ON
l.nop=m.nop LEFT JOIN owner_state as d ON d.id_state=l.id_state
where l.id_state='$current_selected_owner_land' AND
l.high_property='$current_selected_status'";
$Query = pg_Query($Sql);
if(pg_num_rows($Query) > 0){
$i=array();
while ($data = pg_fetch_assoc($Query)){
$data_a[$data['id']][] = $data;
}
return $data_a;
}
public function load_building_all6($current_selected_status){
$Sql="SELECT b.* ,f.family_no,c.name FROM building b LEFT JOIN
building_family f ON b.id=f.id_building LEFT JOIN citizen c ON
c.nik=b.nik LEFT JOIN clans as k on c.clan_id=k.clan_id LEFT JOIN
citizen_status as j on c.status_id=j.status_id LEFT JOIN
land_proprietary as m on m.nik=c.nik LEFT JOIN land as l ON
l.nop=m.nop LEFT JOIN owner_state as d ON d.id_state=l.id_state
where l.high_property='$current_selected_status'";
$Query = pg_Query($Sql);
if(pg_num_rows($Query) > 0){
$i=array();
while ($data = pg_fetch_assoc($Query)){
$data_a[$data['id']][] = $data;
}
return $data_a;
}
```

```

}

public function
load_building_all3($current_selected_clan,$current_selected_owner,$
current_selected_status){
$sql="SELECT b.* ,f.family_no,c.name FROM building b LEFT JOIN
building_family f ON b.id=f.id_building LEFT JOIN citizen c ON
c.nik=b.nik LEFT JOIN clans as k on c.clan_id=k.clan_id LEFT JOIN
citizen_status as j on c.status_id=j.status_id LEFT JOIN
land_proprietary as m on m.nik=c.nik LEFT JOIN land as l ON
l.nop=m.nop LEFT JOIN owner_state as d ON d.id_state=l.id_state
where MD5(c.clan_id::teks)='".$current_selected_clan' AND
l.high_property='".$current_selected_status."'";
$Query = pg_Query($sql);
if(pg_num_rows($Query) > 0){
$i=array();
while ($data = pg_fetch_assoc($Query)){
$data_a[$data['id']][] = $data;
}
return $data_a;
}
public function
load_building_all7($current_selected_owner,$current_selected_status
){
$sql="SELECT b.* ,f.family_no,c.name FROM building b LEFT JOIN
building_family f ON b.id=f.id_building LEFT JOIN citizen c ON
c.nik=b.nik LEFT JOIN clans as k on c.clan_id=k.clan_id LEFT JOIN
citizen_status as j on c.status_id=j.status_id LEFT JOIN
land_proprietary as m on m.nik=c.nik LEFT JOIN land as l ON
l.nop=m.nop LEFT JOIN owner_state as d ON d.id_state=l.id_state
where c.status_id='".$current_selected_owner' AND
l.high_property='".$current_selected_status."'";
$Query = pg_Query($sql);
if(pg_num_rows($Query) > 0){
$i=array();
while ($data = pg_fetch_assoc($Query)){
$data_a[$data['id']][] = $data;
}
return $data_a;
}
public function load_building_all8($current_selected_owner){
$sql="SELECT b.* ,f.family_no,c.name FROM building b LEFT JOIN
building_family f ON b.id=f.id_building LEFT JOIN citizen c ON
c.nik=b.nik LEFT JOIN clans as k on c.clan_id=k.clan_id LEFT JOIN
citizen_status as j on c.status_id=j.status_id LEFT JOIN
land_proprietary as m on m.nik=c.nik LEFT JOIN land as l ON
l.nop=m.nop LEFT JOIN owner_state as d ON d.id_state=l.id_state
where c.status_id='".$current_selected_owner."'";
$Query = pg_Query($sql);
if(pg_num_rows($Query) > 0){
$i=array();
while ($data = pg_fetch_assoc($Query)){
$data_a[$data['id']][] = $data;
}
return $data_a;
}

```

```

}

public function
load_building_all2($current_selected_clan,$current_selected_owner_l
and,$current_selected_status){
$sql="SELECT b.* ,f.family_no,c.name FROM building b LEFT JOIN
building_family f ON b.id=f.id_building LEFT JOIN citizen c ON
c.nik=b.nik LEFT JOIN clans as k on c.clan_id=k.clan_id LEFT JOIN
citizen_status as j on c.status_id=j.status_id LEFT JOIN
land_proprietary as m on m.nik=c.nik LEFT JOIN land as l ON
l.nop=m.nop LEFT JOIN owner_state as d ON d.id_state=l.id_state
where MD5(c.clan_id::teks)='".$current_selected_clan' AND
l.id_state='".$current_selected_owner_land' AND
l.high_property='".$current_selected_status."'";
$Query = pg_Query($sql);
if(pg_num_rows($Query) > 0){
$i=array();
while ($data = pg_fetch_assoc($Query)){
$data_a[$data['id']][] = $data;
}
return $data_a;
}
public function
load_building_all($current_selected_clan,$current_selected_owner,$c
urrent_selected_owner_land,$current_selected_status){
$sql="SELECT b.* ,f.family_no,c.name FROM building b LEFT JOIN
building_family f ON b.id=f.id_building LEFT JOIN citizen c ON
c.nik=b.nik LEFT JOIN clans as k on c.clan_id=k.clan_id LEFT JOIN
citizen_status as j on c.status_id=j.status_id LEFT JOIN
land_proprietary as m on m.nik=c.nik LEFT JOIN land as l ON
l.nop=m.nop LEFT JOIN owner_state as d ON d.id_state=l.id_state
where MD5(c.clan_id::teks)='".$current_selected_clan' AND
c.status_id='".$current_selected_owner' AND
l.id_state='".$current_selected_owner_land' AND
l.high_property='".$current_selected_status."'";
$Query = pg_Query($sql);
if(pg_num_rows($Query) > 0){
$i=array();
while ($data = pg_fetch_assoc($Query)){
$data_a[$data['id']][] = $data;
}
return $data_a;
}
public function
load_building_all4($current_selected_clan,$current_selected_owner,$
current_selected_owner_land){
$sql="SELECT b.* ,f.family_no,c.name FROM building b LEFT JOIN
building_family f ON b.id=f.id_building LEFT JOIN citizen c ON
c.nik=b.nik LEFT JOIN clans as k on c.clan_id=k.clan_id LEFT JOIN
citizen_status as j on c.status_id=j.status_id LEFT JOIN
land_proprietary as m on m.nik=c.nik LEFT JOIN land as l ON
l.nop=m.nop LEFT JOIN owner_state as d ON d.id_state=l.id_state
where MD5(c.clan_id::teks)='".$current_selected_clan' AND

```

```

c.status_id='$current_selected_owner' AND
l.id_state='$current_selected_owner_land';
$Query = pg_Query($sql);
if(pg_num_rows($Query) > 0){
$i=array();
while ($data = pg_fetch_assoc($Query)){
$data_a[$data['id']][] = $data;
}
return $data_a;
}}
// Menampilkan List Bangunan Berupa Peta
// File Proses.php
else if($do == 'g_map_building_clan'){
header('Content-Type: application/json');
$current_selected_clan=$_GET['current_selected_clan'];
$current_selected_owner=$_GET['current_selected_owner'];
$current_selected_owner_land=$_GET['current_selected_owner_land'];
$current_selected_status=$_GET['current_selected_status'];
if($current_selected_clan == 'all' && $current_selected_owner ==
'all' && $current_selected_owner_land == 'all' &&
$current_selected_status == 'all'){
$m = new building();
$data = $m->load_building_map();
echo json_encode($data);
}
else if($current_selected_clan == 'all' && $current_selected_owner !=
'all' && $current_selected_owner_land != 'all' &&
$current_selected_status != 'all'){
$m = new building();
$data = $m->load_map_building_all1($current_selected_owner,
$current_selected_owner_land,$current_selected_status );
echo json_encode($data);
}
else if($current_selected_clan == 'all' && $current_selected_owner !=
'all' && $current_selected_owner_land == 'all' &&
$current_selected_status == 'all'){
$m = new building();
$data = $m->load_map_building_all17($current_selected_owner );
echo json_encode($data);
}
else if($current_selected_clan == 'all' && $current_selected_owner ==
'all' && $current_selected_owner_land != 'all' &&
$current_selected_status == 'all'){
$m = new building();
$data = $m->load_map_building_all3($current_selected_owner_land );
echo json_encode($data);
}
else if($current_selected_clan == 'all' && $current_selected_owner ==
'all' && $current_selected_owner_land == 'all' &&
$current_selected_status != 'all'){
$m = new building();
$data = $m->load_map_building_all4($current_selected_status);
echo json_encode($data);
}
}

```

```

else if($current_selected_clan == 'all' && $current_selected_owner ==
'all' && $current_selected_owner_land != 'all' &&
$current_selected_status != 'all'){
$m = new building();
$data = $m-
>load_map_building_all15($current_selected_owner_land,$current_selec
ted_status);
echo json_encode($data);
}
else if(strlen($current_selected_clan) == 32 &&
$current_selected_owner == 'all' && $current_selected_owner_land ==
'all' && $current_selected_status == 'all'){
$m = new building();
$data = $m->load_map_building_all10($current_selected_clan);
echo json_encode($data);
}
else if(strlen($current_selected_clan) == 32 &&
$current_selected_owner != 'all' && $current_selected_owner_land ==
'all' && $current_selected_status == 'all'){
$m = new building();
$data = $m-
>load_map_building_all11($current_selected_clan,$current_selected_o
wner);
echo json_encode($data);
}
else if(strlen($current_selected_clan) == 32 &&
$current_selected_owner == 'all' && $current_selected_owner_land !=
'all' && $current_selected_status == 'all'){
$m = new building();
$data = $m-
>load_map_building_all12($current_selected_clan,$current_selected_o
wner_land);
echo json_encode($data);
}
else if(strlen($current_selected_clan) == 32 &&
$current_selected_owner == 'all' && $current_selected_owner_land ==
'all' && $current_selected_status != 'all'){
$m = new building();
$data = $m-
>load_map_building_all13($current_selected_clan,$current_selected_s
tatus);
echo json_encode($data);
}
else if(strlen($current_selected_clan) == 32 &&
$current_selected_owner == 'all' && $current_selected_owner_land !=
'all' && $current_selected_status != 'all'){
$m = new building();
$data = $m-
>load_map_building_all14($current_selected_clan,$current_selected_o
wner_land,$current_selected_status);
echo json_encode($data);
}
else if(strlen($current_selected_clan) == 32 &&
$current_selected_owner != 'all' && $current_selected_owner_land !=
'all' && $current_selected_status != 'all'){

```

c. Contoh Luaran Program

```

$m = new building();
$data = $m-
>load_map_building_all15($current_selected_clan,$current_selected_o
wner,$current_selected_owner_land,$current_selected_status);
echo json_encode($data);
}
else{
echo 0;
}
-----
// file Class.php
public function load_map_building_map() {
$ssql="SELECT ST_AsGeoJSON(geom) As geometry,
ST_Y(ST_CENTROID(geom)) AS lat, ST_X(ST_CENTROID(geom)) AS lng,
b.* ,f.family_no,c.name ,case when MD5(c.clan_id::teks)= 'all' then
0 else 1 end as a FROM building b LEFT JOIN building_family f ON
b.id=f.id_building LEFT JOIN citizen c ON c.family_no=f.family_no
LEFT JOIN citizen_status AS cs ON c.status_id = cs.status_id";
Query = pg_Query($ssql);
if(pg_num_rows($Query) > 0){
while ($data = pg_fetch_assoc($Query)){
$data_a[] = $data;
}
return $data_a;
}
public function load_map_building_all1($current_selected_owner,
$current_selected_owner_land,$current_selected_status){
$ssql="SELECT ST_AsGeoJSON(b.geom) As geometry,
ST_Y(ST_CENTROID(b.geom)) AS lat, ST_X(ST_CENTROID(b.geom)) AS lng,
b.* ,f.family_no,c.name ,case when
c.status_id=' $current_selected_owner' AND l.id_state='
$current_selected_owner_land' AND
l.high_property=' $current_selected_status' then 1 else 0 end as a
FROM building b LEFT JOIN building_family f ON b.id=f.id_building
LEFT JOIN citizen c ON c.nik=b.nik LEFT JOIN clans as k on
c.clan_id=k.clan_id LEFT JOIN citizen_status as j on
c.status_id=j.status_id LEFT JOIN land_proprietary as m on
m.nik=c.nik LEFT JOIN land as l ON l.nop=m.nop LEFT JOIN
owner_state as d ON d.id_state=l.id_state";
$Query = pg_Query($ssql);
if(pg_num_rows($Query) > 0){
while ($data = pg_fetch_assoc($Query)){
$data_a[] = $data;
}
return $data_a;
}
public function
load_map_building_all15($current_selected_clan,$current_selected_ow
ner,$current_selected_owner_land,$current_selected_status){
$ssql="SELECT ST_AsGeoJSON(b.geom) As geometry,
ST_Y(ST_CENTROID(b.geom)) AS lat, ST_X(ST_CENTROID(b.geom)) AS lng,
b.* ,f.family_no,c.name ,case when
MD5(c.clan_id::teks)=' $current_selected_clan' AND
l.id_state=' $current_selected_owner_land' AND
l.high_property=' $current_selected_status' then 1 else 0 end as a
FROM building b LEFT JOIN building_family f ON b.id=f.id_building
LEFT JOIN citizen c ON c.nik=b.nik LEFT JOIN clans as k on
c.clan_id=k.clan_id LEFT JOIN citizen_status as j on
c.status_id=j.status_id LEFT JOIN land_proprietary as m on
m.nik=c.nik LEFT JOIN land as l ON l.nop=m.nop LEFT JOIN
owner_state as d ON d.id_state=l.id_state";
$Query = pg_Query($ssql);
if(pg_num_rows($Query) > 0){
while ($data = pg_fetch_assoc($Query)){

```

```

l.high_property=' $current_selected_status' then 1 else 0 end as a
FROM building b LEFT JOIN building_family f ON b.id=f.id_building
LEFT JOIN citizen c ON c.nik=b.nik LEFT JOIN clans as k on
c.clan_id=k.clan_id LEFT JOIN citizen_status as j on
c.status_id=j.status_id LEFT JOIN land_proprietary as m on
m.nik=c.nik LEFT JOIN land as l ON l.nop=m.nop LEFT JOIN
owner_state as d ON d.id_state=l.id_state";
$Query = pg_Query($ssql);
if(pg_num_rows($Query) > 0){
while ($data = pg_fetch_assoc($Query)){
$data_a[] = $data;
}
return $data_a;
}
public function
load_map_building_all14($current_selected_clan,$current_selected_ow
ner_land,$current_selected_status){
$ssql="SELECT ST_AsGeoJSON(b.geom) As geometry,
ST_Y(ST_CENTROID(b.geom)) AS lat, ST_X(ST_CENTROID(b.geom)) AS lng,
b.* ,f.family_no,c.name ,case when
MD5(c.clan_id::teks)=' $current_selected_clan' AND
c.status_id=' $current_selected_owner' AND
l.id_state=' $current_selected_owner_land' AND
l.high_property=' $current_selected_status' then 1 else 0 end as a
FROM building b LEFT JOIN building_family f ON b.id=f.id_building
LEFT JOIN citizen c ON c.nik=b.nik LEFT JOIN clans as k on
c.clan_id=k.clan_id LEFT JOIN citizen_status as j on
c.status_id=j.status_id LEFT JOIN land_proprietary as m on
m.nik=c.nik LEFT JOIN land as l ON l.nop=m.nop LEFT JOIN
owner_state as d ON d.id_state=l.id_state";
$Query = pg_Query($ssql);
if(pg_num_rows($Query) > 0){
while ($data = pg_fetch_assoc($Query)){
$data_a[] = $data;
}
return $data_a;
}
public function
load_map_building_all13($current_selected_clan,$current_selected_st
atus){
$ssql="SELECT ST_AsGeoJSON(b.geom) As geometry,
ST_Y(ST_CENTROID(b.geom)) AS lat, ST_X(ST_CENTROID(b.geom)) AS lng,
b.* ,f.family_no,c.name ,case when
MD5(c.clan_id::teks)=' $current_selected_clan' AND
l.high_property=' $current_selected_status' then 1 else 0 end as a
FROM building b LEFT JOIN building_family f ON b.id=f.id_building
LEFT JOIN citizen c ON c.nik=b.nik LEFT JOIN clans as k on
c.clan_id=k.clan_id LEFT JOIN citizen_status as j on
c.status_id=j.status_id LEFT JOIN land_proprietary as m on
m.nik=c.nik LEFT JOIN land as l ON l.nop=m.nop LEFT JOIN
owner_state as d ON d.id_state=l.id_state";
$Query = pg_Query($ssql);
if(pg_num_rows($Query) > 0){
while ($data = pg_fetch_assoc($Query)){

```

```

$data_a[] = $data;
}
return $data_a;
}
public function
load_map_building_all12($current_selected_clan,$current_selected_owner_land){
$ssql="SELECT ST_AsGeoJSON(b.geom) As geometry,
ST_Y(ST_CENTROID(b.geom)) AS lat, ST_X(ST_CENTROID(b.geom)) AS lng,
b.* ,f.family_no,c.name ,case when
MD5(c.clan_id::teks)=' $current_selected_clan' AND l.id_state=
'$current_selected_owner_land' then 1 else 0 end as a   FROM
building b LEFT JOIN building_family f ON b.id=f.id_building LEFT
JOIN citizen c ON c.nik=b.nik LEFT JOIN clans as k on
c.clan_id=k.clan_id LEFT JOIN citizen_status as j on
c.status_id=j.status_id LEFT JOIN land_proprietary as m on
m.nik=c.nik LEFT JOIN land as l ON l.nop=m.nop LEFT JOIN
owner_state as d ON d.id_state=l.id_state";
$Query = pg_Query($ssql);
if(pg_num_rows($Query) > 0){
while ($data = pg_fetch_assoc($Query)){
$data_a[] = $data;
}
return $data_a;
}
public function
load_map_building_all11($current_selected_clan,$current_selected_owner){
$ssql="SELECT ST_AsGeoJSON(b.geom) As geometry,
ST_Y(ST_CENTROID(b.geom)) AS lat, ST_X(ST_CENTROID(b.geom)) AS lng,
b.* ,f.family_no,c.name ,case when
MD5(c.clan_id::teks)=' $current_selected_clan' AND
c.status_id=' $current_selected_owner' then 1 else 0 end as a   FROM
building b LEFT JOIN building_family f ON b.id=f.id_building LEFT
JOIN citizen c ON c.nik=b.nik LEFT JOIN clans as k on
c.clan_id=k.clan_id LEFT JOIN citizen_status as j on
c.status_id=j.status_id LEFT JOIN land_proprietary as m on
m.nik=c.nik LEFT JOIN land as l ON l.nop=m.nop LEFT JOIN
owner_state as d ON d.id_state=l.id_state";
$Query = pg_Query($ssql);
if(pg_num_rows($Query) > 0){
while ($data = pg_fetch_assoc($Query)){
$data_a[] = $data;
}
return $data_a;
}
public function load_map_building_all10($current_selected_clan){
$ssql="SELECT ST_AsGeoJSON(b.geom) As geometry,
ST_Y(ST_CENTROID(b.geom)) AS lat, ST_X(ST_CENTROID(b.geom)) AS lng,
b.* ,f.family_no,c.name ,case when
MD5(c.clan_id::teks)=' $current_selected_clan' then 1 else 0 end as
a   FROM building b LEFT JOIN building_family f ON
b.id=f.id_building LEFT JOIN citizen c ON c.nik=b.nik LEFT JOIN
clans as k on c.clan_id=k.clan_id LEFT JOIN citizen_status as j on
c.status_id=j.status_id LEFT JOIN land_proprietary as m on

```

```

m.nik=c.nik LEFT JOIN land as l ON l.nop=m.nop LEFT JOIN
owner_state as d ON d.id_state=l.id_state";
$Query = pg_Query($ssql);
if(pg_num_rows($Query) > 0){
while ($data = pg_fetch_assoc($Query)){
$data_a[] = $data;
}
return $data_a;
}
public function
load_map_building_all15($current_selected_owner_land,$current_selected_status){
$ssql="SELECT ST_AsGeoJSON(b.geom) As geometry,
ST_Y(ST_CENTROID(b.geom)) AS lat, ST_X(ST_CENTROID(b.geom)) AS lng,
b.* ,f.family_no,c.name ,case when
l.id_state=' $current_selected_owner_land' AND
l.high_property=' $current_selected_status' then 1 else 0 end as a
FROM building b LEFT JOIN building_family f ON b.id=f.id_building
LEFT JOIN citizen c ON c.nik=b.nik LEFT JOIN clans as k on
c.clan_id=k.clan_id LEFT JOIN citizen_status as j on
c.status_id=j.status_id LEFT JOIN land_proprietary as m on
m.nik=c.nik LEFT JOIN land as l ON l.nop=m.nop LEFT JOIN
owner_state as d ON d.id_state=l.id_state";
$Query = pg_Query($ssql);
if(pg_num_rows($Query) > 0){
while ($data = pg_fetch_assoc($Query)){
$data_a[] = $data;
}
return $data_a;
}
public function load_map_building_all14($current_selected_status){
$ssql="SELECT ST_AsGeoJSON(b.geom) As geometry,
ST_Y(ST_CENTROID(b.geom)) AS lat, ST_X(ST_CENTROID(b.geom)) AS lng,
b.* ,f.family_no,c.name ,case when
l.high_property=' $current_selected_status' then 1 else 0 end as a
FROM building b LEFT JOIN building_family f ON b.id=f.id_building
LEFT JOIN citizen c ON c.nik=b.nik LEFT JOIN clans as k on
c.clan_id=k.clan_id LEFT JOIN citizen_status as j on
c.status_id=j.status_id LEFT JOIN land_proprietary as m on
m.nik=c.nik LEFT JOIN land as l ON l.nop=m.nop LEFT JOIN
owner_state as d ON d.id_state=l.id_state";
$Query = pg_Query($ssql);
if(pg_num_rows($Query) > 0){
while ($data = pg_fetch_assoc($Query)){
$data_a[] = $data;
}
return $data_a;
}
public function
load_map_building_all13($current_selected_owner_land){
$ssql="SELECT ST_AsGeoJSON(b.geom) As geometry,
ST_Y(ST_CENTROID(b.geom)) AS lat, ST_X(ST_CENTROID(b.geom)) AS lng,
b.* ,f.family_no,c.name ,case when l.id_state='
$current_selected_owner_land' then 1 else 0 end as a   FROM
building b LEFT JOIN building_family f ON b.id=f.id_building LEFT

```


```

JOIN citizen c ON c.nik=b.nik LEFT JOIN clans as k on
c.clan_id=k.clan_id LEFT JOIN citizen_status as j on
c.status_id=j.status_id LEFT JOIN land_proprietary as m on
m.nik=c.nik LEFT JOIN land as l ON l.nop=m.nop LEFT JOIN
owner_state as d ON d.id_state=l.id_state";
$Query = pg_Query($sql);
if(pg_num_rows($Query) > 0){
while ($data = pg_fetch_assoc($Query)){
$data_a[] = $data;
}
return $data_a;
}
public function load_map_building_all7($current_selected_owner) {
$sql="SELECT ST_AsGeoJSON(geom) As geometry,
ST_Y(ST_CENTROID(geom)) AS lat, ST_X(ST_CENTROID(b.geom)) AS lng,
b.*,f.family_no,c.name ,case when
c.status_id!='$current_selected_owner' then 1 else 0 end as a
FROM building b LEFT JOIN building_family f ON b.id=f.id_building
LEFT JOIN citizen c ON c.nik=b.nik LEFT JOIN clans as k on
c.clan_id=k.clan_id LEFT JOIN citizen_status as j on
c.status_id=j.status_id";
$Query = pg_Query($sql);
if(pg_num_rows($Query) > 0){
while ($data = pg_fetch_assoc($Query)){
$data_a[] = $data;
}
return $data_a;
}
}

```

No	No Rumah	Pemilik	Lokasi	NIK	Action
1	A001	Syahril	Padang Luar	1301032104680004	
2	A002	Syahril	Padang Luar	1301032104680004	
3	A004	Ismail	Jalan Utama	1306060103890006	

Gambar 13. Hasil Menampilkan List Bangunan Berupa Informasi Teks



Gambar 14. Hasil List Bangunan Berupa Peta

6. Mengelola Data Building History

a. Use Case Skenario

Tabel 11. Skenario Menampilkan Data Building History

Use Case Name	Menampilkan data Building history
Participating Actor	User
Flow Of Events	<ol style="list-style-type: none"> 1. User memilih menu land 2. Sistem akan menampilkan sub menu 3. User memilih menu land history 4. Sistem akan menampilkan data building history
Entry condition	User telah login
Exit Condition	User dapat melihat informasi building history

Tabel 12. Prosedur Menginputkan Data Building History

Use Case Name	Menambah Data Building history
Participating Actor	User
Flow Of Events	<ol style="list-style-type: none"> 1. User memilih menu building 2. Sistem akan menampilkan sub menu 3. User memilih menu building history 4. Sistem akan menampilkan menu building history 5. User mengklik button displacement of building owner

	<p>6. Sistem akan form menambah data <i>building history</i></p> <p>7. User mengisi form dan memilih button save</p> <p>8. Sistem akan menyimpan perubahan dalam <i>database</i></p>
<i>Entry condition</i>	User telah login
<i>Exit Condition</i>	Sistem menyimpan perubahan data ke <i>database</i> dan membuka kembali halaman <i>building history</i>

a. Kode Program

```
// Menampilkan Data Building History
//method untuk query menampilkan data Building history
public function load_building_owner(){
    $sql="SELECT b.no_house, p.name, bo.id_building
    FROM building as b LEFT JOIN building_owner as bo on
    b.id=bo.id_building LEFT JOIN pemilik as p ON p.nik=
    bo.pemilik_id order by name asc ";
    $query = pg_query($sql);
    if(pg_num_rows($query) > 0){
        while ($data = pg_fetch_assoc($query)) {
            $data_a[] = $data;
        }
        return $data_a;
    }
}

// Menginputkan Data Building History

//method untuk query menginputkan data history land
public function insert_building_history($data){
    $sqlICN="INSERT INTO building_owner(pemilik_id, tgl, state,
    coment, id_building) VALUES ";
    $sqlICN.=(".". ".$data['pemilik_id']."' , '".$data['tgl']."' , '".$data['state']."' , '".$data['coment']."' , '".$data['id_building']."' ");
    $sql=$sqlICN.';';
    $query = pg_query($sql);
    if($query){
        return 1;
    }else{
        return 0;
    }
}
```

b. Contoh Luaran Program

No	ID Building	Date	Name	State	Comment
6	A091	2017-06-04	Asnelli	Warisan Adat	
7	A091	2017-06-04	Wisnar Dinar	Warisan Adat	
11	A091	2016-08-01	Abrar	Warisan Adat	
12	A091	2016-08-01	Wisnar Dinar	Warisan Adat	

Gambar 15. Hasil Menampilkan Data Building History

Gambar 16. Hasil Menginputkan Data BuildingHistory

7. Pencarian Kepemilikan Tanah Berdasarkan Nomor Penduduk

a. Use Case Skenario

Tabel 13. Skenario Pencarian Data Kepemilikan Tanah Berdasarkan Nomor Penduduk

Berupa Informasi Teks

<i>Use case name</i>	Pencarian Data Kepemilikan Tanah Berdasarkan Nomor Penduduk Berupa Informasi Teks
<i>Participating Actor</i>	<i>User</i>
<i>Flow Of Events</i>	<ol style="list-style-type: none"> 1. User memilih menu <i>citizen</i> 2. Sistem akan menampilkan sub menu

	<p>3. User memilih menu <i>land proprietary search</i></p> <p>4. Sistem akan menampilkan menu <i>land proprietary search</i></p> <p>5. User memasukan nomor penduduk</p> <p>6. Sistem akan menampilkan informasi teks mengenai data penduduk</p>
<i>Entry condition</i>	<i>User</i> telah login
<i>Exit Condition</i>	<i>User</i> dapat melihat informasi teks mengenai data penduduk yang diinginkan
<i>Alternative Course</i>	<p>1. User memilih menu <i>land</i></p> <p>2. Sistem akan menampilkan sub menu</p> <p>3. User memilih menu <i>land search</i></p> <p>4. Sistem akan menampilkan menu <i>land proprietary search</i></p> <p>5. User memasukan nomor penduduk</p> <p>6. Sistem akan menampilkan "Data Not Found"</p>

Tabel 14. Skenario Pencarian Data Kepemilikan Tanah Berdasarkan Nomor Penduduk

Berupa Peta

<i>Use case name</i>	Pencarian Data Kepemilikan Tanah Berdasarkan Nomor Penduduk Berupa Peta
<i>Participating Actor</i>	<i>User</i>
<i>Flow Of Events</i>	<p>a. User memilih menu <i>citizen</i></p> <p>b. Sistem akan menampilkan sub menu</p> <p>c. User memilih menu <i>land proprietary search</i></p> <p>d. Sistem akan menampilkan menu <i>land proprietary search</i></p> <p>e. User memasukan nomor penduduk</p> <p>f. Sistem akan menampilkan data nomor penduduk</p>

	<p>g. User memilih tab <i>map</i></p> <p>7. Sistem akan menampilkan lokasi berdasarkan nomor penduduk yang diinputkan</p>
<i>Entry condition</i>	<i>User</i> telah login
<i>Exit Condition</i>	<i>User</i> dapat melihat lokasi berdasarkan nomor penduduk

b. Kode Program

```
// Pencarian Data Penduduk Berdasarkan Nomor Penduduk Berupa Informasi Teks Untuk Kepemilikan Tanah
```

```
// Method untuk memanggil data dari database menggunakan  
// bahasa pemrograman php
```

```
public function find_owner($id){  
    // query pencarian data penduduk berdasarkan nomor penduduk  
    $sql = "SELECT ci.nik, ci.name, ci.phone, ci.gender,  
    EXTRACT(YEAR FROM AGE(ci.born_date)) AS age, cs.name AS  
    status, cl.name AS clan FROM citizen AS ci LEFT JOIN  
    citizen_status AS cs ON ci.status_id = cs.status_id LEFT JOIN  
    clans AS cl on ci.clan_id = cl.clan_id WHERE ci.nik = '$id'";  
    $Query = pg_Query($sql);  
    if(pg_num_rows($Query) > 0){  
        //generate informasi data penduduk;  
        $result = pg_fetch_assoc($Query)  
        $data['nik'] = $result['nik'];  
        $data['name'] = $result['name'];  
        $data['phone'] = $result['phone'];  
        $data['gender'] = $result['gender'];  
        $data['age'] = $result['age'];  
        $data['status'] = $result['status'];  
        $data['clan'] = $result['clan'];  
        //memilih tanah yang berdasarkan data penduduk yang  
        //diinputkan;  
        $sql = "SELECT la.nop, la.high_property, la.tax_value,  
        la.pawning, la.land_size, la.building_size FROM  
        land_proprietary AS lp LEFT JOIN land AS la ON lp.nop = la.nop  
        WHERE lp.nik = '".$result['nik']."'";  
        $Query_object = pg_Query($sql);  
        $data_object = null;  
        if(pg_num_rows($Query_object)>0){  
            $data_object = array();  
            while ($result_sub = pg_fetch_assoc($Query_object)) {  
                //memilih pemilik dari tanah;  
                $sql = "SELECT sci.nik, sci.name AS name, EXTRACT(YEAR FROM  
                AGE(sci.born_date)) AS age FROM land_proprietary AS slp LEFT
```

c. Contoh luaran program

```

JOIN citizen AS sci ON slp.nik = sci.nik WHERE slp.nop =
'".$result_sub['nop']."'";
$Query_owner = pg_Query($sql);
$data_owner = null;
if(pg_num_rows($Query_owner)){
$data_owner = array();
while ($result_sub_re = pg_fetch_assoc($Query_owner)) {
$data_owner[] = $result_sub_re;
}
}
$data_object[] = array(
'nop' => $result_sub['nop'],
'high_property' => $result_sub['high_property'],
'tax_value' => $result_sub['tax_value'],
'pawning' => $result_sub['pawning'],
'land_size' => $result_sub['land_size'],
'building_size' => $result_sub['building_size'],
'owner' => $data_owner,
);
}
$data['object'] = $data_object;
return $data;
}
else{
return 0;
}


// Pencarian Data Penduduk Berdasarkan Nomor Penduduk Untuk Kepemilikan Tanah
// Berupa Peta
//method mendapatkan layer dari object bangunan berdasarkan nomor penduduk
public function find_object_tax($id){
$sql = "SELECT la.nop, la.high_property, la.pawning,
la.tax_value, la.land_size, la.building_size, (SELECT
array_to_json(array_agg(f)) FROM (SELECT ci.nik, ci.name AS
name, cs.name AS status, EXTRACT(YEAR FROM AGE(ci.born_date))
AS age FROM tax_subject AS ts LEFT JOIN citizen AS ci ON
ts.nik = ci.nik LEFT JOIN citizen_status AS cs ON ci.status_id
= cs.status_id WHERE ts.nop = la.nop) AS f) AS subject,
jo.name AS address FROM land AS la, jorong AS jo WHERE
ST_CONTAINS(jo.geom, ST_CENTROID(la.geom)) AND la.nop =
'$id'";
$Query = pg_Query($sql);
if(pg_num_rows($Query) > 0){
$result = pg_fetch_assoc($Query);
$data['nop'] = $result['nop'];
$data['high_property'] = $result['high_property'];
$data['pawning'] = $result['pawning'];
$data['tax_value'] = $result['tax_value'];
$data['land_size'] = $result['land_size'];
$data['building_size'] = $result['building_size'];
$data['subject'] = json_decode($result['subject']);
$data['address'] = $result['address'];
return $data;
}
else{
}
}

```


```

        return 0;
    }
}


```




Gambar 17. Hasil Data Normal Pencarian Data Kepemilikan Tanah Berdasarkan Nomor Penduduk Berupa Informasi Teks



Gambar 18. Land Information



Gambar 19. House Information



Gambar 20. Hasil Pencarian Data Kepemilikan Tanah Berdasarkan Nomor Penduduk Berupa Peta

8. Pencarian Data Kepemilikan Bangunan Berdasarkan Nomor Penduduk

a. Use Case Skenario

Tabel 15. Skenario Pencarian Data Kepemilikan Bangunan Berdasarkan Nomor Penduduk Berupa Informasi Teks

<i>Use case name</i>	Pencarian Data Kepemilikan Bangunan Berdasarkan Nomor Penduduk Berupa Informasi Teks
<i>Participating Actor</i>	User
<i>Flow Of Events</i>	<ol style="list-style-type: none"> 1. User memilih menu <i>citizen</i> 2. Sistem akan menampilkan sub menu 3. User memilih sub menu <i>building owner search</i> 4. Sistem akan menampilkan sub menu <i>building owner search</i> 5. User memasukan nomor penduduk 6. Sistem akan menampilkan informasi teks mengenai nomor penduduk
<i>Entry condition</i>	User telah login
<i>Exit Condition</i>	User dapat melihat informasi teks mengenai data penduduk yang diinginkan

<i>Alternative Course</i>	5. User memilih menu <i>citizen</i>
	6. Sistem akan menampilkan sub menu
	7. User memilih sub menu <i>building owner search</i>
	8. Sistem akan menampilkan sub menu <i>building owner search</i>
	7. User memasukan nomor penduduk
	8. Sistem akan menampilkan "Data Not Found"

Tabel 16. Skenario Pencarian Data Kepemilikan Bangunan Berdasarkan Nomor Penduduk Berupa Peta


<i>Use case name</i>	Pencarian Data Kepemilikan Tanah Berdasarkan Nomor Penduduk Berupa Peta
<i>Participating Actor</i>	User
<i>Flow Of Events</i>	<ol style="list-style-type: none"> a. User memilih menu <i>citizen</i> b. Sistem akan menampilkan sub menu c. User memilih menu <i>building owner search</i> d. Sistem akan menampilkan menu <i>building owner search</i> e. User memasukan nomor penduduk f. Sistem akan menampilkan data nomor penduduk g. User memilih tab <i>map</i> 8. Sistem akan menampilkan lokasi berdasarkan nomor penduduk
<i>Entry condition</i>	User telah login
<i>Exit Condition</i>	User dapat melihat lokasi berdasarkan nomor penduduk

b. Kode Program


```
// Pencarian Data Penduduk Berdasarkan Nomor Penduduk Berupa Informasi
// Teks Untuk Kepemilikan Bangunan
// Method untuk memanggil data dari database menggunakan bahasa
// pemrograman php
public function find_owner1($id){
//query pencarian data penduduk
$sql = "SELECT ci.nik, ci.name, ci.phone, ci.gender,
EXTRACT(YEAR FROM AGE(ci.born_date)) AS age, cs.name AS status,
cl.name AS clan, bd.id, ci.family_no FROM building as bd left
join building_family as bf ON bd.id=bf.id_building left join
citizen AS ci on ci.family_no=bf.family_no LEFT JOIN
citizen_status AS cs ON ci.status_id = cs.status_id LEFT JOIN
clans AS cl on ci.clan_id = cl.clan_id WHERE ci.nik ='$id'";
$query = pg_query($sql);
if(pg_num_rows($query) > 0){
//generate informasi data penduduk;
$result = pg_fetch_assoc($query);
$data['nik'] = $result['nik'];
$data['name'] = $result['name'];
$data['phone'] = $result['phone'];
$data['gender'] = $result['gender'];
$data['age'] = $result['age'];
$data['status'] = $result['status'];
$data['clan'] = $result['clan'];
$data['id'] = $result['id'];
$data['family_no'] = $result['family_no'];
//memilih tanah yang dimiliki oleh data penduduk;
$sql = "SELECT la.nop, la.high_property, la.tax_value,
la.pawning, la.land_size, la.building_size FROM
land_proprietary As lp LEFT JOIN land AS la ON lp.nop = la.nop
WHERE lp.nik = '".$result['nik']."' ";
$query_object = pg_query($sql);
$data_object = null;
if(pg_num_rows($query_object)>0){
$data_object = array();
while ($result_sub = pg_fetch_assoc($query_object)) {
//memilih pemilik tanah;
$sql = "SELECT sci.nik, sci.name AS name, EXTRACT(YEAR FROM
AGE(sci.born_date)) AS age FROM land_proprietary As slp LEFT
JOIN citizen AS sci ON slp.nik = sci.nik WHERE slp.nop =
'".$result_sub['nop']."' ";
$query_owner = pg_query($sql);
$data_owner = null;
if(pg_num_rows($query_owner)){
$data_owner = array();
while ($result_sub_re = pg_fetch_assoc($query_owner)) {
$data_owner[] = $result_sub_re;
}
$data_object[] = array(
'nop' => $result_sub['nop'],
'high_property' => $result_sub['high_property'],
'tax_value' => $result_sub['tax_value'],
)
```

```
'pawning' => $result_sub['pawning'],
'land_size' => $result_sub['land_size'],
'building_size' => $result_sub['building_size'],
'owner' => $data_owner,
); }
$data['object'] = $data_object;
//mencari informasi pemilik tanah
$sql = "SELECT ci.family_no, COUNT(ci.nik) AS resident
FROM citizen AS ci LEFT JOIN building_family as b ON
ci.family_no=b.family_no LEFT JOIN building as c ON
b.id_building=c.id WHERE id = '".$result['id']."' GROUP BY
ci.family_no";
$query_fcn = pg_query($sql);
$data_fcn = null;
if(pg_num_rows($query_fcn)>0){
$data_fcn = array();
while ($result_sub_fcn = pg_fetch_assoc($query_fcn)) {
$data_fcn[] = $result_sub_fcn;
}
$data['resident'] = $data_fcn;
return $data;
}
else{
return 0;
}
// Pencarian Data Penduduk Berdasarkan Nomor Penduduk Untuk Kepemilikan
// Bangunan Berupa Peta
//method mendapatkan layer dari object bangunan berdasarkan
//nomor penduduk
public function object_layer_owner($owner_id){
$sql = "SELECT ST_AsGeoJSON(la.geom) AS geometry, la.nop,
ST_Y(ST_CENTROID(la.geom)) AS lat, ST_X(ST_CENTROID(la.geom))
AS lng FROM land AS la LEFT JOIN land_proprietary AS lp ON
la.nop = lp.nop WHERE lp.nik = '$owner_id'";
$geojson = array(
'type' => 'FeatureCollection',
'features' => array()
);
$query = pg_query($sql);
if(pg_num_rows($query)==0) return 0;
while($edge=pg_fetch_assoc($query)){
$feature = array(
"type" => 'Feature',
'geometry' => json_decode($edge['geometry'], true),
'properties' => array(
'object' => $edge['nop'],
'center' => array(
'lat' => $edge['lat'],
'lng' => $edge['lng']
));
array_push($geojson['features'], $feature);
}
return $geojson;
}
```


c. Contoh Luaran Program



Gambar 21. Hasil Data Normal Pencarian Data Kepemilikan Bangunan Berdasarkan Nomor Penduduk Berupa Informasi Teks



Gambar 22. Family Information



Gambar 23. Hasil Pencarian Data Kepemilikan Bangunan Berdasarkan Nomor Penduduk Berupa Peta

9. Pencarian Data Penduduk Berdasarkan Nomor Penduduk

a. Use Case Skenario

Tabel 17. Skenario Pencarian Data Penduduk Berdasarkan Nomor Penduduk Berupa Informasi Teks

<i>Use Case Name</i>	Pencarian Penduduk Berdasarkan Nomor Penduduk Berupa Informasi Teks
<i>Participating Actor</i>	<i>User</i>
<i>Flow Of Events</i>	<ol style="list-style-type: none"> 1. <i>User</i> memilih menu <i>citizen</i> 2. Sistem akan menampilkan submenu 3. <i>User</i> memilih submenu <i>population search</i> 4. Sistem akan menampilkan submenu <i>population search</i> 5. <i>User</i> menginputkan salah satu nomor penduduk 6. Sistem menampilkan data berdasarkan nomor yang diinputkan
<i>Entry condition</i>	<i>User</i> telah login
<i>Exit Condition</i>	Sistem Menampilkan data berdasarkan kriteria yang dipilih

Tabel 18. Skenario Pencarian Data Penduduk Berdasarkan Nomor penduduk Berupa Informasi Peta

<i>Use Case Name</i>	Pencarian Penduduk Berdasarkan Nomor Penduduk Berupa Peta
<i>Participating Actor</i>	<i>User</i>
<i>Flow Of Events</i>	<ol style="list-style-type: none"> 1. <i>User</i> memilih menu <i>citizen</i> 2. Sistem akan menampilkan submenu 3. <i>User</i> memilih submenu <i>population search</i> 4. Sistem akan menampilkan submenu <i>population search</i> 5. <i>User</i> menginputkan salah satu nomor penduduk


	6. Sistem menampilkan informasi berdasarkan nomor penduduk yang diinputkan
	7. User memilih tab <i>map</i>
	8. Sistem menampilkan halaman tab <i>map</i>
<i>Entry condition</i>	User telah login
<i>Exit Condition</i>	Sistem Menampilkan data bedasarkan kriteria yang dipilih

b. Kode Program


```
// Pencarian Data Penduduk Berdasarkan Nomor Penduduk Berupa
// Informasi Teks
// Method untuk memanggil data dari database menggunakan
// bahasa pemrograman php
public function find_family($family_id){
    $sql = "SELECT re.id_building, COUNT(re.family_no) AS amount,
    ci.family_no, ci.address, ci.name, cl.name as clan,
    ci.gender, EXTRACT(YEAR FROM AGE(ci.born_date)) AS age FROM
    building_family AS re LEFT JOIN citizen AS ci ON
    re.family_no= ci.family_no left join clans as cl on
    cl.clan_id=ci.clan_id WHERE ci.nik ='".$family_id."' GROUP
    BY re.id_building, ci.family_no,ci.address, ci.name, cl.name,
    ci.gender, ci.born_date";
    $query = pg_query($sql);
    if(pg_num_rows($query) > 0){
        $result = pg_fetch_assoc($query);
        $data['family_no'] = $result['family_no'];
        $data['id_building'] = $result['id_building'];
        $data['amount'] = $result['amount'];
        $data['addres'] = $result['address'];
        $data['name'] = $result['name'];
        $data['clan'] = $result['clan'];
        $data['gender'] = $result['gender'];
        $data['age'] = $result['age'];
        // mencari daftar anggota
        $sql = "SELECT ci.nik, ci.name, ci.gender, EXTRACT(YEAR FROM
        AGE(ci.born_date)) AS age, cl.name AS clan FROM citizen AS ci
        LEFT JOIN clans AS cl ON ci.clan_id=cl.clan_id WHERE
        ci.family_no ='".$result['family_no']."' ";
        $query_people = pg_query($sql);
        $data_people = null;
        if(pg_num_rows($query_people)>0){
            $data_people = array();
            while ($result_sub = pg_fetch_assoc($query_people)) {
                $data_people[] = $result_sub;
            }
        }
        $data['people'] = $data_people;
        return $data;
    }
}
```

```
}
else{
    return 0;
}
// Pencarian Data Penduduk Berdasarkan Nomor Penduduk Berupa Peta
// method mendapatkan layer dari object bangunan berdasarkan
// nomor penduduk
public function family_layer($family_id){
    $sql = "SELECT ST_AsGeoJSON(ho.geom) As geometry, ho.id,
    ST_Y(ST_CENTROID(ho.geom)) AS lat, ST_X(ST_CENTROID(ho.geom))
    AS lng FROM building As ho left join building_family as bf on
    bf.id_building=ho.id left join citizen as ci on
    ci.family_no=bf.family_no WHERE ci.nik = '$family_id'";
    $geojson = array(
        'type' => 'FeatureCollection',
        'features' => array()
    );
    $query = pg_query($sql);
    if(pg_num_rows($query)==0) return 0;
    while($edge=pg_fetch_assoc($query)){
        $feature = array(
            'type' => 'Feature',
            'geometry' => json_decode($edge['geometry'], true),
            'properties' => array(
                'object' => $edge['id'],
                'center' => array(
                    'lat' => $edge['lat'],
                    'lng' => $edge['lng']
                )));
        array_push($geojson['features'], $feature);
    }
    return $geojson;
}
```

c. Contoh luaran program



Gambar 24. Hasil Data Normal Pencarian Data Penduduk Berdasarkan Nomor Penduduk Berupa *Informasi Teks*



Gambar 25. Hasil Pencarian Data Penduduk Berdasarkan Nomor Penduduk Berupa Peta

10. Mengelola Data Kelahiran

a. Use Case Skenario

Tabel 19. Prosedur Fungsional Menampilkan Peta Berdasarkan List Data Kelahiran


Use Case Name	Menampilkan Persebaran Peta Kelahiran
Participating Actor	User
Flow Of Events	<ol style="list-style-type: none"> 1. User memilih menu <i>citizen</i> 2. Sistem menampilkan submenu dari menu <i>citizen</i> 3. User memilih menu data kelahiran 4. Sistem menampilkan halaman data kelahiran 5. User memilih tab <i>map</i> 6. Sistem akan menampilkan halaman <i>map</i> 7. User memilih kriteria yang telah disediakan dan mengklik button <i>search</i> 8. Sistem menampilkan persebaran peta berdasarkan kriteria yang di pilih sebelumnya

Entry condition	User telah login
Exit Condition	Sistem menampilkan persebaran peta


b. Kode program

```
// Menampilkan Peta Berdasarkan Kelahiran
// method untuk menampilkan layer berdasarkan data kelahiran
public function status_map_birth_clan($selected,$year,$m1,$m2) {
    $sql = "SELECT ST_AsGeoJSON(geom) As geometry,
    ST_Y(ST_CENTROID(geom)) AS lat, ST_X(ST_CENTROID(geom)) AS lng,
    building.id,birth_date, case when MD5(citizen.clan_id::teks) =
    '$selected' AND EXTRACT (MONTH from out_come_date) >= '$m1' AND
    EXTRACT (MONTH from out_come_date) <= '$m2' AND EXTRACT (year from
    birth_data.birth_date)!= '$year' or EXTRACT (year from
    birth_data.birth_date) is NULL then 0 else 1 end as a FROM
    birth_data right join citizen on
    birth_data.family_no=citizen.family_no right join building on
    building.family_no=citizen.family_no order by birth_date";
    $Query = pg_Query($sql);
    if(pg_num_rows($Query) > 0) {
        while ($data = pg_fetch_assoc($Query)) {
            $data_a[] = $data;
        }
        return $data_a;
    }else{
        return 0;
    }
}
```


c. Contoh Luraran Program




Gambar 26. Hasil Menampilkan List data Kelahiran



Gambar 27. Hasil Menampilkan Peta Berdasarkan *List* data Kelahiran



Gambar 28. Data Pada Pencarian Data Penduduk Berdasarkan Nomor Penduduk (1)



Gambar 29. Data Pada Pencarian Data Penduduk Berdasarkan Nomor Penduduk(2)

11. Mengelola Data Kematian

a. Use Case Skenario

Tabel 20. Skenario Menampilkan Peta Berdasarkan Data Kematian

<i>Use Case Name</i>	Menampilkan Persebaran Peta Kematian
<i>Participating Actor</i>	<i>User</i>
<i>Flow Of Events</i>	<ol style="list-style-type: none"> 1. <i>User</i> memilih menu <i>citizen</i> 2. Sistem menampilkan submenu dari menu <i>citizen</i> 3. <i>User</i> memilih menu data kematian 4. Sistem menampilkan halaman data kematian 5. <i>User</i> memilih tab <i>map</i> 6. Sistem akan menampilkan halaman <i>map</i> 7. <i>User</i> memilih kriteria yang telah disediakan dan mengklik button <i>search</i> 8. Sistem menampilkan persebaran peta berdasarkan kriteria yang di pilih sebelumnya
<i>Entry condition</i>	<i>User</i> telah login

Exit Condition	Sistem menampilkan persebaran peta
----------------	------------------------------------

b. Kode Program

```
// Menampilkan Peta Berdasarkan Kematian Penduduk
// method untuk menampilkan layer berdasarkan data kematian
public function
status_map_dead_clan($selected,$year,$m1,$m2){
$sql = "SELECT ST_AsGeoJSON(geom) As geometry,
ST_Y(ST_CENTROID(geom)) AS lat, ST_X(ST_CENTROID(geom)) AS
lng, building.id,death_date, case when
MD5(citizen.clan_id::teks) = '$selected' AND EXTRACT (MONTH
from mortality_data.death_date) >= '$m1' AND EXTRACT (MONTH
from mortality_data.death_date) <= '$m2' AND EXTRACT (year
from mortality_data.death_date) = '$year' AND EXTRACT (year
from mortality_data.death_date) is NOT NULL then 1 else 0 end
as a FROM mortality_data right join citizen on
mortality_data.nik=citizen.nik right join building on
building.nik=citizen.nik order by death_date ";
$query = pg_Query($sql);
if(pg_num_rows($query) > 0){
while ($data = pg_fetch_assoc($query)){
$data_a[] = $data;
}
return $data_a;
}
else{
return 0;
}}
```


c. Contoh Luaran Program

The screenshot shows the 'Death Data' section of the application. At the top, there are date selection dropdowns for Year (2017), From Month (1), Until Month (12), and a 'Select' button. Below this is a 'Show' dropdown menu with options like Clans, Payobadar, and others. A 'Death Data' tab is selected, showing a table with two entries:


No.	Identity Card Number	Name	Date Died	Action
1	1399001704876608	Adikara Gunarto	2017-11-15	
2	1399007872331900	Ade Hutapea S.Pt	2017-07-17	

At the bottom, it says 'Showing 1 to 2 of 2 entries'.


Gambar 6. Hasil Menampilkan Data Kematian



Gambar 7. Hasil Menampilkan Peta Berdasarkan Data Kematian



Gambar 8. Data Menggunakan Data Penduduk Berdasarkan Nomor Penduduk (1)



Gambar 9. Data Menggunakan Data Penduduk Berdasarkan Nomor Penduduk

12. Mengelola Perpindahan Penduduk

a. Use case skenario

Tabel 21. Skenario Menampilkan Peta Berdasarkan Data Perpindahan Penduduk


Use Case Name	Menampilkan Persebaran Peta Perpindahan
Participating Actor	User
Flow Of Events	<ol style="list-style-type: none"> 1. User memilih menu citizen 2. Sistem menampilkan submenu dari menu citizen 3. User memilih menu data perpindahan 4. Sistem menampilkan halaman data perpindahan 5. User memilih tab map 6. Sistem akan menampilkan halaman map 7. User memilih kriteria yang telah disediakan dan mengklik button search 8. Sistem menampilkan persebaran peta berdasarkan kriteria yang di pilih sebelumnya

Entry condition	User telah login
Exit Condition	Sistem menampilkan persebaran peta


b. Kode Program

```
// Menampilkan Peta Berdasarkan Perpindahan
// method untuk menampilkan layer berdasarkan data perpindahan
public function
status_map_outcome_clan($selected,$year,$m1,$m2) {
$sql = "SELECT ST_AsGeoJSON(geom) AS geometry,
ST_Y(ST_CENTROID(geom)) AS lat, ST_X(ST_CENTROID(geom)) AS lng,
building.id,out_come_date, case when MD5(citizen.clan_id)::text
= '$selected' AND EXTRACT (MONTH from out_come_date) >= '$m1'
AND EXTRACT (MONTH from out_come_date) <= '$m2' AND EXTRACT
(year from out_come.out_come_date) = '$year' AND EXTRACT (year
from out_come.out_come_date) is NOT NULL then 1 else 0 end as
a FROM out_come right join citizen on out_come.nik=citizen.nik
right join building on building.nik=citizen.nik order by
out_come_date ";
$query = pg_Query($sql);
if(pg_num_rows($query) > 0) {
while ($data = pg_fetch_assoc($query)) {
$data_a[] = $data;
}
else{
return 0;
}
}
return $data_a;
}
```


c. Contoh Luaran Program




Gambar 10. Hasil Menampilkan Data Perpindahan Penduduk



Gambar 11. Hasil Menampilkan Peta Berdasarkan Data Perpindahan Penduduk



Gambar 13. Data Menggunakan Pencarian Data Penduduk Berdasarkan Nomor Penduduk(2)



Gambar 12. Data Menggunakan Pencarian Data Penduduk Berdasarkan Nomor Penduduk (1)